



Burke Wall Base

Mannington
COMMERCIAL



Cover: BurkeBase® - 204 Gray (ACCORD color), Confluence Modular Carpet - Optimism 81010, Security 63014 (Installation - Vertical Ashlar)
Above: BurkeBase® - 820 Daffodil, Abstracted Strie LVT - Core ANT400



Accord Colors

The Accord System offers 36 color choices that span the entire spectrum of premium rubber flooring products, including wall base, tiles, stair treads and finishing accessories.

TS Vulcanized Thermoset Rubber, TP Coextruded Thermoplastic Vinyl, and TV Coextruded Thermoplastic Vinyl

Wall Base Type	2.5" x .080" toeless & coved	2.5" x 1/8" toeless & coved	4" x .080" toeless & coved	4" x 1/8" toeless & coved	4.5" x 1/8" toeless & coved	6" x .080" toeless & coved	6" x 1/8" toeless & coved	10" x 1/8" toeless only	4' lengths toeless & coved	100' seamless rolls toeless & coved	100 color offering (includes 36 Accord colors)	95 color offering (includes 36 Accord colors)
Type TV - Matte	*	*	*	*	*	*	*		*	*	*	
Type TP - Matte		*		*	*		*		*	*	*	
Type TS - Satin		*		*			*	*	*	select colors, coved only		*

** Some limitations in availability - see spec page for full details. Inside and outside corners also available.*

Custom colors available for a minimum.

	Almond	403		Off White	244		Beach Sand	030		Light Gray	208		Frosted Jade	210		Mocha	597
	Cream	205		Baja	519		Sky Gray	663		Carmine Gray	674		Daffodil	820		Mango	070
	Desert Sand	118		Gray Beige	209		Jackalope	190		Ash	603		Sugar Snap	055		Geranium	966
	Ginger	503		Sandy Tan	112		Gray	204		Gray Blue	672		Mountain Meadow	077		Peacock	120
	Tumbleweed	033		Clay	527		Moonbeam	050		Rocky	660		Dark Forest	331		Ocean Blue	115
	Pecan	504		Brown	502		BlackBrown	523		Charcoal	217		Black	701		Navy	875

Performance and Features

Available Heights/Sizes	BurkeBase Type TS 1/8" *	BurkeBase Type TP 1/8" **	BurkeBase Type TV 1/8" **	BurkeBase Type TV .080" **
	2.5" (64 mm)	2.5" (64 mm)	2.5" (64 mm)	2.5" (64 mm)
	4" (102 mm)	4" (102 mm)	4" (102 mm)	4" (102 mm)
	6" (152 mm)	4.5" (114 mm)	4.5" (114 mm)	6" (152 mm)
	10" (254 mm) (Toeless only)	6" (152 mm)	6" (152 mm)	
	Coved or Toeless	Coved or Toeless	Coved or Toeless	Coved or Toeless

Warranty This product is backed by our Limited 5 Year Commercial Warranty.

Corners BurkeBase® Type TS factory molded corners are available in all profile sizes except 10" and toeless corners. Must be ordered at time of wall base order to ensure color match.

BurkeBase® Type TP/TV pre-formed corners are available in all profile sizes. Must be ordered at time of wall base order to ensure color match.

Custom Colors Minimums apply.

Please make final selection for all colors from actual product samples.

For samples and information visit manningtoncommercial.com or call 800.241.2262.

Thermoset Rubber

BurkeBase® Rubber Wall Base
Type TS Benefits

- Vulcanized thermoset rubber to prevent shrinkage or expansion
- Molded to provide dimensional stability
- Smooth satin finish and inherent flexibility helps hide substrate irregularities
- Available in 4' molded lengths
- 100' seamless rolls available in colors 204, 206, 208, 209, 217, 502, 523, 597, 701 and 727
- 95 standard colors including 36 ACCORD colors

Thermoplastic Rubber

BurkeBase® Rubber Wall Base
Type TP Benefits

- Heavy gauge rubber base
- Flexible formulation easily forms to curves and corners for clean installation
- Will not fade or crack
- Scuff and scratch resistant
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors including 36 ACCORD colors

Vinyl

BurkeBase® Vinyl Wall Base
Type TV Benefits

- Engineered for heavy traffic and high maintenance areas
- Scuff and abrasion resistant
- Tough matte finish helps hide substrate irregularities
- Available in .080" and .125" gauges
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors including 36 ACCORD colors

* Type TS Coved and Toeless 4' lengths available in 2.5", 4", 6", and 10" heights (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523, 597, 701, and 727, in 4" height only.

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5", 4", 4.5", and 6" heights. Both available in .080" & 1/8" thickness.

BurkeBase®

Style	BurkeBase Type TS 1/8" *	BurkeBase Type TP 1/8" ** (Non-Ortho Phthalate)
Construction	Thermoset Rubber	Thermoplastic Rubber
Finish	Satin	Matte
Classification	ASTM F1861 Type TS, Group 1	ASTM F1861 Type TP, Group 1
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Coved or Toeless 2.5" (64 mm) 4" (102 mm) 6" (152 mm) 10" (254 mm) Toeless Only	Coved or Toeless 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm)
Colors	95 (36 are Accord)	100 (36 are Accord)
Packaging	25-4' pieces = 100' per carton Toeless 10" = 15-4' pieces	1-100' continuous roll or 25-4' pieces
Weight Per Carton – 2.5" / 4" / 4.5 " / 6" / 10"	Coved = 27/39/53 lbs. Toeless = 24/39/50 lbs. Toeless 10" = 51 lbs.	Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs.
Weight Per Carton – Corners	Coved = 3/4/7 lbs. Toeless = 3/4/7 lbs. Toeless 1/8" = 3/4/9 lbs.	Coved = 3/4/9 lbs. Coved = 3/4/9 lbs.
Corners (must be ordered at time of wall base order to ensure color match)	Factory molded corners available	Factory pre-formed corners available
Adhesive	Burke BR-101	Burke BR-101
Testing		
Flexibility (ASTM F137)	Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.	
Flammability (ASTM E-84)	Class B rating with smoke density of 150 - 200	
Heat Resistance (ASTM E648)	Passes, Class I, .45 watts/cm ²	
Smoke Generation (ASTM E662)	Maximum Specific Optical Density of 450 or less	
Environmental Data		
Indoor Air Quality	FloorScore Certified	
LEED Scoreboard	May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials	
Manufacturing	Calhoun, GA USA	
Warranty		
	Limited 5 Year Commercial Warranty	

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved and Toeless 4' lengths available in 2.5", 4", 6", and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523, 597, 701 and 727 in 4" height only.

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5", 4", 4.5", and 6" heights. Both available in .080 & 1/8" thickness.

BurkeBase®

Style	BurkeBase Type TV 1/8" ** (Non-Ortho Phthalate)	BurkeBase Type TV .080" ** (Non-Ortho Phthalate)
Construction	Vinyl	Vinyl
Finish	Matte	Matte
Classification	ASTM F1861 Type TV, Group 1	ASTM F1861 Type TV, Group 1
Total Thickness	1/8" (3.2 mm)	.080" (2.0 mm) & 1/8" (3.2 mm)
Profile	Coved or Toeless	Coved or Toeless
Sizes	2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm)	2.5" (64 mm) 4" (102 mm) 6" (152 mm)
Colors	100 (36 are Accord)	100 (36 are Accord)
Packaging	1-100' continuous roll or 25-4' pieces	1-100' continuous roll or 25-4' pieces
Weight Per Carton – 2.5" / 4" / 4.5 " / 6" / 10"	Coved (1/8") = 24/37/41/53 lbs. Toeless (1/8") = 23/36/41/52 lbs.	Coved (.080") = 19/27/41/42 lbs. Toeless (.080") = 17/25/41/39 lbs.
Weight Per Carton – Corners	Coved = 3/4/9 lbs. Toeless = 3/4/9 lbs.	Coved (.080") = 3/3/8 lbs. Toeless (.080") = 2/3/7 lbs.
Corners (must be ordered at time of wall base order to ensure color match)	Factory pre-formed corners available	Factory pre-formed corners available
Adhesive	Burke BR-101	Burke BR-101
Testing		
Flexibility (ASTM F137)	Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.	
Static Load ASTM F910	500 psi	
Flammability ASTM E648	.45 watts/cm², Passes (Class I)	
Slip Resistance ASTM C1028	<450 – Passes	
Environmental Data		
Indoor Air Quality	FloorScore Certified	
LEED Scoreboard	May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials	
Manufacturing	Calhoun, GA (USA)	
Warranty		
	Limited 5 Year Commercial Warranty	Limited 5 Year Commercial Warranty

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved and Toeless 4' lengths available in 2.5", 4", 6", and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523 and 597 in 4" height only.

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5", 4", 4.5", and 6" heights. Both available in .080 & 1/8" thickness.