



---

Connected Collection

**Mannington**  
COMMERCIAL





**Cover: Social Modular** - Synergy 15213  
**Installation** - Vertical Ashlar  
**Above: Profile Modular** - Collective 42207  
**Installation** - Horizontal Brick Ashlar





Offline Loop Modular - Collective 42207  
Installation - Vertical Ashlar





**Offline Modular** - Collective 42207  
**Installation** - Vertical Ashlar





**Online Modular** - Synergy 15213  
**Installation** - Horizontal Brick Ashlar





Media Modular - Collective 42207  
Installation - Horizontal Brick Ashlar



Connected Collection Accent Colors

With the Connected Collection, you can select a custom accent stripe color for both the Media Modular and Social Modular styles. Choose from 30 Antron® Lumena™ yarn colors in brights and neutrals to perfectly coordinate your carpet with any design palette.

Custom accent stripe requires 500 yd<sup>2</sup> minimum.

					
Chablis486	Bean Sprout297	Raw Silk278	Warm Pewter276	Silver170	Granite152
					
Pigeon144	Brownstone203	Peppercorn130	Obsidian114	Dark Rosewood341	Majestic Purple852
					
Autumn Glory381	Cayenne391	Raspberry333	Dress Blues738	Blue Velvet770	Slate Blue753
					
Atlantis693	Tungsten625	Blackened Teal731	Saguaro516	Jungle Green527	Chartreuse484
					
Bold Gold490	Medallion487	Firecracker401	Copperplate424	Spice465	Gold470

With industry-leading fiber systems and superior manufacturing, our carpets look better and last up to 75% longer than any other carpet in the marketplace.



### Proven by Third-Party Testing

Every carpet we make at Mannington Commercial is third-party tested and proven to exceed industry standards in appearance retention, texture retention, fire safety factors and static generation, and our modular carpet exceeds industry standards in dimensional stability – so you can be sure that the carpet you specify will perform for years to come.

#### Easier to Maintain

- > Antron® nylon features a unique, hollow-filament shape for exceptional soil hiding and cleanability.
- > XGUARD® Stain Resistant Technology provides long-term stain resistance for our space dye products.
- > ColorSafe® Bleach Resistant Technology resists color fade-out from bleach spills for our space dye products.
- > Moisture-barrier backings are built to withstand aggressive wet cleanings.

#### Backing Advantages

- > Infinity® 2 Modular backing provides exceptional performance with a moisture barrier.
- > Infinity® 2 Modular backing offers superior tuft bind and dimensional stability with a limited lifetime warranty.

#### Sustainable Solutions

- > All of our carpets have EPDs and HPDs.
- > Infinity® 2 Modular backing is CRI Green Label Plus Certified and NSF/ANSI 140 Gold Certified
- > Infinity® 2 Modular backing contains recycled content

#### 3.5 TARR

- > Mannington Commercial carpets are made with a minimum 3.5 TARR (Texture Appearance Retention Rating), meaning any carpet you specify will be able to withstand severe traffic. The 3.5 TARR on our carpets is tested and verified by an independent lab.






Antron® type 6,6 nylon is engineered with stain and soil protection and offers long-lasting texture retention. Antron® fiber is designed for a more effective, longer-lasting clean, helping to reduce your total cost of ownership and contributing to a cleaner facility.


#### Better Shape, Better Performance

Antron® fiber has a sturdy, 4-hole hollow filament shape that makes it more resistant to crushing and matting than type 6 nylon fiber.





Antron® Fiber  
4-hole hollow filament

< 1.5 MR (Modification Ratio)




Common Type 6 Nylon  
trilobal filament

+ 2 MR (Modification Ratio)




#### Soil Resistance

Unlike a typical type 6 nylon fiber, the unique shape and low modification ratio of Antron® fiber does not provide anywhere for dirt to collect. This ensures better soil release during vacuuming and hot water extraction. Between cleanings, the 4-hole hollow filament structure also diffuses light, reducing the appearance of soil and helping the carpet look cleaner.



Antron® Fiber  
4-hole hollow filament



Common Type 6 Nylon  
trilobal filament

#### XGUARD® Stain Resistance

Carpets with Mannington Commercial's proprietary XGUARD® stain resistant technology offer the highest level of performance in permanent stain resistance. Protection against common stains as well as ease of maintenance result in long-term appearance retention and extend the life of the carpet.

#### ColorSafe® Bleach Resistance

Mannington Commercial's ColorSafe® bleach resistant technology works from within the fiber to protect carpets against bleach and maintain colorfastness. Carpets with ColorSafe® are protected from occasional spills and drips of diluted disinfecting bleach solution, ensuring that colors remain bright and that the carpet can withstand the toughest cleaning conditions.



## Connected Collection

Style	Media Modular (Non-Ortho Phthalate)	Offline Modular (Non-Ortho Phthalate)	Offline Loop Modular (Non-Ortho Phthalate)
Construction	Tip-sheared Patterned Loop	Tip-sheared Patterned Loop	Patterned Loop
Face Fiber	Antron® Lumena™	Antron® Lumena™	Antron® Lumena™
	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	9.66 (38.03 per 10 cm)	9.66 (38.03 per 10 cm)	9.66 (38.03 per 10 cm)
Density	6,468 (240.34 kg/m³)	6,545 (243.20 kg/m³)	6,655 (247.29 kg/m³)
Pile Thickness	0.128" (3.25 mm)	0.121" (3.07 mm)	0.119" (3.02 mm)
Weight	23 oz/yd² (780 g/m²)	22 oz/yd² (746 g/m²)	22 oz/yd² (746 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular	Infinity® 2 Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	16	16	16
Packaging	6.22 yd² / 14 Tiles	6.22 yd² / 14 Tiles	6.22 yd² / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar	Vertical Ashlar	Vertical Ashlar
<b>Testing</b>			
Dimensional Stability (Aachen Test)	Passes		
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²		
Smoke Density (ASTM E662)	Passes - ≤ 450		
Methenamine Pill Test (ASTM D2859)	Passes		
Hexapod (ASTM D5252) TARR	3.5		
<b>Environmental Data</b>			
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold		
Recycled Content	Contains recycled content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	EPD, HPD		
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered		
<b>Warranty</b>			
	Limited Lifetime Wear & Backing Warranty		
	Limited 15 Year XGUARD® Stain Resistant Warranty		
	Limited 15 Year ColorSafe® Bleach Resistant Warranty		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.



Connected Collection

Style	Online Modular (Non-Ortho Phthalate)	Profile Modular (Non-Ortho Phthalate)	Social Modular (Non-Ortho Phthalate)
Construction	Tip-sheared Patterned Loop	Tip-sheared Patterned Loop	Tip-sheared Patterned Loop
Face Fiber	Antron® Lumena™	Antron® Lumena™	Antron® Lumena™
	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	9.66 (38.03 per 10 cm)	9.66 (38.03 per 10 cm)	9.66 (38.03 per 10 cm)
Density	6,468 (240.34 kg/m³)	6,786 (252.15 kg/m³)	6,545 (243.20 kg/m³)
Pile Thickness	0.128" (3.25 mm)	0.122" (3.10 mm)	0.121" (3.07 mm)
Weight	23 oz/yd² (780 g/m²)	23 oz/yd² (780 g/m²)	22 oz/yd² (746 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular	Infinity® 2 Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	16	16	16
Pattern Repeat	N/A	N/A	N/A
Packaging	6.22 yd² / 14 Tiles	6.22 yd² / 14 Tiles	6.22 yd² / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar	Horizontal Brick Ashlar and Vertical Ashlar	Horizontal Brick Ashlar and Vertical Ashlar
Testing			
Dimensional Stability (Aachen Test)	Passes		
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²		
Smoke Density (ASTM E662)	Passes - ≤ 450		
Methenamine Pill Test (ASTM D2859)	Passes		
Hexapod (ASTM D5252) TARR	3.5		
Environmental Data			
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold		
Recycled Content	Contains recycled content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	EPD, HPD		
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRC5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered		
Warranty			
	Limited Lifetime Wear & Backing Warranty		
	Limited 15 Year XGUARD® Stain Resistant Warranty		
	Limited 15 Year ColorSafe® Bleach Resistant Warranty		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.