

MANNINGTON WALL BASE COLLECTION









Cover: Optimum Edge — Toffee 921

Above: Premium Edge — Silver Pine 922











PERFORMANCE AND FEATURES










		Optimum Edge®	Optimum Edge® 100	Premium Edge™	Mannington Edge™
	AVAILABLE HEIGHTS/SIZE	2 1/2" (64 mm) 4" (102 mm) 6" (152 mm) Coved or Toeless	4" (102 mm) Coved Available in ten colors**	2 1/2" (64 mm) 4" (102 mm) 4 1/2" (114 mm) 6" (152 mm) Coved or Toeless	2 1/2" (64 mm) 4" (102 mm) 4 1/2" (114 mm) 6" (152 mm) Coved or Toeless
	WARRANTY	This product is backed by our Limited 5 Year Commercial Warranty.			
	CORNERS	Mannington corners available [Optimum Edge factory molded corners – specify (jobsite wrapped) or (molded) corners], [Premium Edge factory pre-formed corners are available – specify (jobsite wrapped) or (factory pre-formed) corners], and [Mannington Edge factory pre-formed corners are available – specify (jobsite wrapped) or (factory pre-formed) corners. Factory-made inside and outside wall base corners must be ordered when the wall base is ordered to insure an exact color match.			
	X P R E S S	When you really need it now. Our innovative delivery program ensures that you get the carpet and hard surface products you need quickly and reliably. With product available to ship within 5 business days, Mannington's new Xpress program leads the industry in service. To see a full list of Mannington's Xpress products, visit www.mannington.com/commercial/xpress.aspx			
** Optimum Edge® 100 is available in ten colors: 901 Night Black, 902 Deep Suede, 903 Dark Chocolate, 904 Bark, 905 Pewter, 907 Stone Gray, 911 Sable, 913 Mineral Gray, 918 Flax, 933 Sandrift					

- Optimum Edge (Type TS), constructed with the highest quality thermoset vulcanized rubber, offers superior dimensional stability. Its molded construction prevents contraction or expansion during or after installation. It is easy to install with a unique top return that ensures a snug wall fit and easily wraps around corners, columns and curved walls. Molded inside and outside corners are available to match various wall base heights. A PVC-free product, its smooth satin luster provides superior appearance retention and complements a wide variety of flooring and wall textures.
- Premium Edge (Type TP) is made with co-extruded thermoplastic rubber specifically formulated to stand up to scuffs and abrasions yet flexible enough for easy installation around curves and corners. This product is of non-phthalate construction. Its smooth matte finish is crack and white-out resistant and will not oxidize or turn brittle. Premium Edge is available in 4' lengths or continuous rolls with pre-formed inside and outside corners to match various wall base heights for smooth transitions.
- An economical choice, Mannington Edge (Type TV) thermoplastic vinyl works for high maintenance areas providing a smooth matte finish that is abrasion resistant. Flexible formulation that easily conforms to irregularities of the wall and can be installed around curves and corners. This product is of non-phthalate construction. Available in 4' lengths or continuous rolls with pre-formed inside and outside corners to match various wall base heights.
- Optimum Edge is available in 2 1/2", 4" and 6" heights with coved or toeless profiles. Premium Edge and Mannington Edge are available in 2 1/2", 4", 4 1/2" and 6" heights with coved or toeless profiles. For color choices, choose from 70 colors including our Sync Color Coordination System which integrates our entire rubber products wall base, rubber tile, stair treads and finishing accessories.



SUSTAINABILITY

	<p>ENERGY LEADERSHIP</p>	<p>With one of the largest solar arrays in the flooring industry (3.3 acres in Salem NJ) and ambitious goals to improve energy efficiency by 25% over ten years, we have an ongoing partnership with the Department of Energy to lead manufacturing into smarter energy use, as well as to reduce related carbon emissions.</p>
	<p>SOLAR ARRAY</p>	<p>At 3.3 acres, we have one of the largest solar arrays in the flooring industry generating 1,000,000 kilowatt hours annually.</p>
	<p>WATER REDUCTION</p>	<p>Water is a precious natural resource and a key component in manufacturing. By investing in technology and a continual emphasis on efficiency and lean manufacturing, we have reduced our water use by more than 35% since 2007. We also actively help protect wetlands in the communities where we make flooring.</p>
	<p>US MANUFACTURING</p>	<p>Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in eight communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.</p>
	<p>3RD PARTY CERTIFICATIONS</p>	<p>Certifications help navigate the world of green marketing claims. So we invest in ISO-14001 and environmentally preferable product certifications including NSF/ANSI-140, NSF/ANSI-332, FloorScore, and Green Label Plus. All of our products may contribute to multiple LEED and Green Globe credits.</p>
	<p>PURPLE MARTINS</p>	<p>In the mid-1980s, we began attracting migrating birds called Purple Martins to our New Jersey manufacturing campus as a more natural alternative to the use of pesticides. This “Purple Martin Project” has proven to be an incredibly environmentally friendly and cost effective way to control insects. Our employees are engaged in the banding and tracking of the birds.</p>
	<p>HONEY BEES</p>	<p>In 2009, as part of an effort to show how an industrial enterprise can co-exist with the agricultural & farming community and positively contribute to both, Mannington’s New Jersey corporate site began to house honeybees, and now have 5 hives in Salem, NJ and 4 in Eustis, FL. The honey bees are thriving and each year we are able to enjoy and share the honey we produce.</p>
	<p>CLIMATE REGISTRY</p>	<p>Mannington is dedicated to reducing our greenhouse gas emissions by 25% over 10 years. Since 2007, a 10% reduction can be attributed to energy efficiencies, process efficiencies, and use of renewable energy. Additional information can be found on thelimitregistry.org.</p>

SPECIFICATIONS

		Optimum Edge®	Optimum Edge® 100	Premium Edge™	Mannington Edge™
	CONSTRUCTION	Thermoset Rubber, Type TS	Thermoset Rubber, Type TS	Thermoplastic Rubber, Type TP	Thermoplastic Vinyl, Type TV
	AVAILABLE HEIGHTS/SIZE	2 1/2" (64 mm) 4" (102 mm) 6" (152 mm) Coved or Toeless	4" (102 mm) Coved Available in ten colors**	2 1/2" (64 mm) 4" (102 mm) 4 1/2" (114 mm) 6" (152 mm) Coved or Toeless	2 1/2" (64 mm) 4" (102 mm) 4 1/2" (114 mm) 6" (152 mm) Coved or Toeless
	OVERALL THICKNESS	1/8" (3.2 mm)	1/8" (3.2 mm)	1/8" (3.2 mm)	.08" (2.0 mm) & 1/8" (3.2 mm)
	PACKAGE COUNT	25-4' pieces = 100' per carton	1-100' continuous roll	1-100' continuous roll or 25-4' pieces	1-100' continuous roll or 25-4' pieces
	AVERAGE WEIGHT PER CARTON 2 1/2" / 4" / 4 1/2" / 6"	Coved = 27/39/53 lbs. Toeless = 24/39/50 lbs.	Coved = 38 lbs.	Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs.	Coved (.08") = 19/27/41/42 lbs. Toeless (.08") = 17/25/41/39 lbs. Coved (1/8") = 24/37/41/53 lbs. Toeless (1/8") = 23/36/41/52 lbs.
	AVERAGE WEIGHT PER CARTON – CORNERS	Coved = 3/4/7 lbs. Toeless = 3/4/7 lbs.	N/A	Coved = 3/4/9 lbs. Toeless = 3/4/9 lbs.	Coved (.08") = 3/3/8 lbs. Toeless (.08") = 2/3/7 lbs. Coved (1/8") = 3/4/9 lbs. Toeless (1/8") = 3/4/9 lbs.
	CORNERS	Factory molded, specify job site wrapped or molded	Specify job site made corners	Factory Pre-formed, specify job site wrapped or preformed	Factory Pre-formed, specify job site wrapped or preformed
	3RD PARTY CERTIFICATIONS	FloorScore			
	XPRESS	When you really need it now. Our innovative delivery program ensures that you get the carpet and hard surface products you need quickly and reliably. With product available to ship within 5 business days, Mannington's Xpress program leads the industry in service. Please refer to www.manningtoncommercial.com to view Xpress products.			

** Optimum Edge® 100 is available in ten colors: 901 Night Black, 902 Deep Suede, 903 Dark Chocolate, 904 Bark, 905 Pewter, 907 Stone Gray, 911 Sable, 913 Mineral Gray, 918 Flax, 933 Sandrift

	Optimum Edge®	Optimum Edge® 100	Premium Edge™	Mannington Edge™
 WARRANTY	This product is backed by our Limited 5 Year Commercial Warranty			
 LEED	Mannington Commercial products may contribute to multiple LEED credits.			
FINISH	Smooth Satin Luster	Smooth Satin Luster	Smooth Matte	Matte
SPECIFICATIONS ASTM (F-1861)	Type TS, Group 1	Type TS, Group 1	Type TP, Group 1	Type TV, Group 1
FLOORING RADIANT PANEL TEST (ASM-E-648)	≥ 0.45 watts/cm ² , Passes — Class 1			
N.B.S. SMOKE CHAMBER TEST (ASTM-E-662)	< 450, Passes			
INSTALLATION ADHESIVE	Mannington MR-101 Acrylic Wall Base Adhesive			



Floor design copyrighted by Mannington Mills, Inc. 2014. For complete specifications, visit www.manningtoncommercial.com.



MANNINGTON
COMMERCIAL

