



Equinox Collection

Mannington
COMMERCIAL



Cover: Light Grid Broadloom - Solstice 12101
Above: Shadow Play Modular - Zenith 15404
Installation - Monolithic





Light Grid Modular - Zenith 15404
Installation - Horizontal Brick Ashlar



Shadow Play Modular - Solstice 12101
Installation - Monolithic



Ecliptic Point Modular - Zenith 15404
Installation - Vertical Ashlar

The Texture of Contrast

Designed in collaboration with London-based industrial design firm Ryan Harc: three richly textured patterns explore the depth of light and shadow, rendered as pure texture and expressed in a high fashion aesthetic. Available in modular and broadloom to tailor to your space.



Equinox Collection

Style	Ecliptic Point Broadloom	Ecliptic Point Modular (Non-Ortho Phthalate)	Light Grid Broadloom
Construction	Textured Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon
Dye Method	Yarn	Yarn	Yarn
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	6.33 (24.92 per 10 cm)	6.33 (24.92 per 10 cm)	6.5 (26.89 per 10 cm)
Density	6,603 (255.94 kg/m ³)	6,603 (255.94 kg/m ³)	6,888 (255.94 kg/m ³)
Pile Thickness	0.169" (4.29 mm)	0.169" (4.29 mm)	0.162" (4.11 mm)
Weight	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)
Backing Type	UltraBac® RE	Infinity® 2 Modular	UltraBac® RE
Size	12' (3.66 m)	24" x 24" (60.96 x 60.96 cm)	12' (3.66 m)
Colors	13	13	13
Pattern Repeat	24" W x 15 1/2" L (60.96 x 39.37 cm)	N/A	24" W x 43" L (60.96 x 109.22 cm)
Packaging	N/A	6.22 yd ² / 14 Tiles	N/A
Adhesive	Ultra Adhesive	Infinity® Adhesive	Ultra Adhesive
Installation Method	N/A	Vertical Ashlar	N/A
Testing			
Dimensional Stability (Aachen Test)	Passes		
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²		
Smoke Density (ASTM E662)	Passes - ≤ 450		
Methenamine Pill Test (ASTM D2859)	Passes		
Hexapod (ASTM D5252) TARR	3.5		
Environmental Data			
NSF/ANSI 140 Certification	UltraBac® RE - Platinum, Infinity® 2 Modular - Gold		
Recycled Content	Contains recycled content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	EPD, HPD		
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRC5 Regional Materials; MRC6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered		
Warranty			
	Limited Lifetime Wear & Backing		
	Limited 15 Year XGUARD® Stain Resistant		
	Limited 15 Year ColorSafe® Bleach Resistant		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Equinox Collection

Style	Light Grid Modular (Non-Ortho Phthalate)	Shadow Play Broadloom	Shadow Play Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon
Dye Method	Yarn	Yarn	Yarn
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	6.83 (26.89 per 10 cm)	6.5 (25.59 per 10 cm)	6.5 (25.59 per 10 cm)
Density	6,888 (255.94 kg/m ³)	6,340 (235.58 kg/m ³)	6,340 (235.58 kg/m ³)
Pile Thickness	0.162" (4.11 mm)	0.176" (4.47 mm)	0.176" (4.47 mm)
Weight	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)
Backing Type	Infinity® 2 Modular	UltraBac® RE	Infinity® 2 Modular
Size	24" x 24" (60.96 x 60.96 cm)	12' (3.66 m)	24" x 24" (60.96 x 60.96 cm)
Colors	13	13	13
Pattern Repeat	N/A	24" W x 79 1/2" L (60.96 x 201.93 cm)	N/A
Packaging	6.22 yd ² / 14 Tiles	N/A	6.22 yd ² / 14 Tiles
Adhesive	Infinity® Adhesive	Ultra Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar	N/A	Monolithic
Testing			
Dimensional Stability (Aachen Test)	Passes		
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²		
Smoke Density (ASTM E662)	Passes - ≤ 450		
Methenamine Pill Test (ASTM D2859)	Passes		
Hexapod (ASTM D5252) TARR	3.5		
Environmental Data			
NSF/ANSI 140 Certification	UltraBac® RE - Platinum, Infinity® 2 Modular - Gold		
Recycled Content	Contains recycled content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	EPD, HPD		
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRC5 Regional Materials; MRC6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered		
Warranty			
	Limited Lifetime Wear & Backing Limited 15 Year XGUARD® Stain Resistant Limited 15 Year ColorSafe® Bleach Resistant		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.