





QUANTUM GUARD® HP: PATENTED PERFORMANCE

- Highest performance commercial urethane finish in the industry
- No polish
- Enhances durability, cleanability, appearance, and slip retardance when compared to standard LVT floors
- Significant reduction in overall lifecycle cost greatly lowers total cost of ownership








MOHS HARDNESS SCALE

10 = Natural Diamond

9 = QGHP

7 = Quartz

2 = Urethane without aluminum oxide




MAINTENANCE
PER SQ. FOOT

REGULAR MAINTENANCE ANNUAL TOTAL



RESTORATIVE MAINTENANCE ANNUAL TOTAL



TOTAL ANNUAL COST PER SQ. FT.




\$0.66 STANDARD LVT



\$0.20 QGHP LVT

CUMULATIVE COST PER SQ. FT. BY YEAR



Break Even on Product and Maintenance Cost Difference Between: LVT VS. QGHP = 2 YEARS

PERFORMANCE AND FEATURES			
	AVAILABLE SIZE	5.8" x 37" nominal	
QGHP	QUANTUM GUARD® HP	The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention, and slip retardance when compared to standard LVT floors – resulting in 70% annual savings in maintenance costs.	
FLOOR ARMOR	FLOORARMOR™	FloorArmor™ is a unique core innovation that delivers a superior combination of benefits. With industry leading commercial product specifications, FloorArmor™ delivers enhanced dimensional stability, ease of installation, superior acoustic properties and outstanding indentation resistance, combined with a product that is virtually waterproof.	
WARRANTY 10 YEAR	WARRANTY	This product is backed by our Limited 10 Year Commercial Warranty, Limited 10 Year No Gap Warranty, and Limited 10 Year Quantum Guard® HP Wear Warranty.	
SUSTAINABILITY			
BETTER PLANTS	ENERGY LEADERSHIP	With one of the largest solar arrays in the flooring industry (3.3 acres in Salem NJ) and ambitious goals to improve energy efficiency by 25% over ten years, we have an ongoing partnership with the Department of Energy to lead manufacturing into smarter energy use, as well as to reduce related carbon emissions.	
	WATER REDUCTION	Water is a precious natural resource and a key component in manufacturing. By investing in technology and a continual emphasis on efficiency and lean manufacturing, we have reduced our water use by 30% company-wide since 2007. We also actively help protect wetlands in the communities where we make flooring.	
*	SOLAR ARRAY	At 3.3 acres, we have one of the largest solar arrays in the flooring industry, generating 1,000,000 kilowatt hours annually.	



ISO 14001

ISO 14001 is a global environmental standard that provides a system for continual improvement in environmental performance.



3RD PARTY CERTIFICATIONS Certifications help navigate the world of green marketing claims. So we invest in ISO-14001 and environmentally preferable product certifications including NSF/ANSI-140, NSF/ANSI-332, FloorScore, and Green Label Plus. All of our products may contribute to multiple LEED and Green Globe credits.



LEED

Mannington Commercial products may contribute to multiple LEED credits.

SUSTAINABILITY

1

PURPLE MARTINS

In the mid-1980s, we began attracting migrating birds called Purple Martins to our New Jersey manufacturing campus as a more natural alternative to the use of pesticides. This "Purple Martin Project" has proven to be an incredibly environmentally friendly and cost effective way to control insects. Our employees are engaged in the banding and tracking of the birds.



HONEYBEES

In 2009, as part of an effort to show how an industrial enterprise can co-exist with the agricultural & farming community and positively contribute to both, Mannington's New Jersey corporate site began to house honeybees, and now have 5 hives in Salem, NJ and 4 in Eustis, FL. The honeybees are thriving and each year we are able to enjoy and share the honey we produce.



CE MARK

Certifies that a product has met EU health, safety, and environmental requirements, which ensure consumer safety. Manufacturers in the European Union (EU) and abroad must meet CE marking requirements where applicable in order to market their products in Europe.

......



CLIMATE REGISTRY

Mannington is dedicated to reducing our greenhouse gas emissions by 25% over 10 years. Since 2007, a 10% reduction can be attributed to energy efficiencies, process efficiencies, and use of renewable energy. Additional information can be found on the climater egistry.org.







SPECIFICATIONS | CITY PARK

SPECIFICATIONS CITY PARK			
Φ¢	CONSTRUCTION	Solid Core construction with micro-beveled edges featuring a FloorArmor™ core and locking technology.	
	AVAILABLE SIZES	5.8" x 37" nominal (148 mm x 940 mm)	
×⊑	WEAR LAYER THICKNESS	20 mil (0.51 mm)	
x	OVERALL THICKNESS	0.236" (6 mm); FloorArmor™ Core 0.197" (5 mm); Sound Abatement Pad 0.039" (1 mm)	
***	PIECES PER CARTON	8 pcs	
*	COVERAGE PER CARTON	11.97 sq. ft.	
	3RD PARTY CERTIFICATIONS	FloorScore	
	LEED	Mannington Commercial products may contribute to multiple LEED credits.	
QGHP	QUANTUM GUARD® HP	The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention, and slip retardance when compared to standard LVT floors - resulting in 70% annual savings in maintenance costs.	
FLOOR ARMOR	FLOORARMOR™	FloorArmor™ is a unique core innovation that delivers a superior combination of benefits. With industry leading commercial product specifications, FloorArmor™ delivers enhanced dimensional stability, ease of installation, superior acoustic properties and outstanding indentation resistance, combined with a product that is virtually waterproof.	
WARRANTY 10 VEAR	WARRANTY	This product is backed by our Limited 10 Year Commercial Warranty, Limited 10 Year No Gap Warranty, and Limited 10 Year Quantum Guard® HP Wear Warranty.	
STATIC LOAD LIMIT		750 PSI	
SPECIFICATIONS (ASTM F3261)		Class 1, Type B, Backing Class B	
HEAT STABILITY (ASTM F1514)		Passes	
STAIN & CHEMICAL RESISTANCE (ASTM F925)		Passes	
COEFFICIENT OF FRICTION (COF)		≥ 0.5 Leather; 0.6 Rubber	
FLOORING RADIANT PANEL (ASTM E648)		≥ 0.45 watts/cm2, Passes (Class 1)	
HUD/FHA REQUIREMENTS		Exceeds	
AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)		Meets or exceeds ADA Guidelines	
N.B.S. SMOKE CHAMBER (ASTM E662)		< 450, Passes	
INSTALLATION ADHESIVE		City Park utilizes a patented locking system that does not require adhesive.	





