

ACCESS | WOOD, STONE & ABSTRACT





COVER: STONE - Linear Stone Shale SX5S3606, ABSTRACT - Linen Weave SX5A3800

WOOD - Shibori Jasmine SX5W7800

ABOVE: STONE - Linear Stone Black SX5S2405



STONE - Linear Stone Shale SX5S3606



ABSTRACT - Linen Weave SX5A3800



WOOD - Ashdown Plum SX5W8000





WOOD - Shibori Jasmine SX5W7800

WOOD - Black Walnut SX5W2534





WOOD - Frosted Oak SX5W5020





PERFORMANCE AND FEATURES

	<p>AVAILABLE SIZES</p>	<p>5.91" x 39.37" (150.1 mm x 1000 mm) 17.7" x 17.7" (449.6 mm x 449.6 mm) All with micro-beveled edges. Sizes are style dependent.</p>
	<p>WARRANTY</p>	<p>Access is backed by our Limited 10 Year Commercial Warranty.</p>

SUSTAINABILITY

	<p>ENERGY LEADERSHIP</p>	<p>With one of the largest solar arrays in the flooring industry (3.3 acres in Salem NJ) and ambitious goals to improve energy efficiency by 25% over ten years, we have an ongoing partnership with the Department of Energy to lead manufacturing into smarter energy use, as well as to reduce related carbon emissions.</p>
	<p>WATER REDUCTION</p>	<p>Water is a precious natural resource and a key component in manufacturing. By investing in technology and a continual emphasis on efficiency and lean manufacturing, we have reduced our water use by 30% company-wide since 2007. We also actively help protect wetlands in the communities where we make flooring.</p>
	<p>SOLAR ARRAY</p>	<p>At 3.3 acres, we have one of the largest solar arrays in the flooring industry, generating 1,000,000 kilowatt hours annually.</p>
	<p>ISO 14001</p>	<p>ISO 14001 is a global environmental standard that provides a system for continual improvement in environmental performance.</p>
	<p>3RD PARTY CERTIFICATIONS</p>	<p>Certifications help navigate the world of green marketing claims. So we invest in ISO-14001 and environmentally preferable product certifications including NSF/ANSI-140, NSF/ANSI-332, FloorScore, and Green Label Plus. All of our products may contribute to multiple LEED and Green Globe credits.</p>
	<p>PURPLE MARTINS</p>	<p>In the mid-1980s, we began attracting migrating birds called Purple Martins to our New Jersey manufacturing campus as a more natural alternative to the use of pesticides. This "Purple Martin Project" has proven to be an incredibly environmentally friendly and cost effective way to control insects. Our employees are engaged in the banding and tracking of the birds.</p>

SUSTAINABILITY

	HONEYBEES	In 2009, as part of an effort to show how an industrial enterprise can co-exist with the agricultural & farming community and positively contribute to both, Mannington's New Jersey corporate site began to house honeybees, and now have 5 hives in Salem, NJ and 4 in Eustis, FL. The honeybees are thriving and each year we are able to enjoy and share the honey we produce.
	CE MARK	Certifies that a product has met EU health, safety, and environmental requirements, which ensure consumer safety. Manufacturers in the European Union (EU) and abroad must meet CE marking requirements where applicable in order to market their products in Europe.
	CLIMATE REGISTRY	Mannington is dedicated to reducing our greenhouse gas emissions by 25% over 10 years. Since 2007, a 10% reduction can be attributed to energy efficiencies, process efficiencies, and use of renewable energy. Additional information can be found on theclimateregistry.org .
	ENVIRONMENTAL PRODUCT DECLARATION	EPDs communicate the comprehensive life cycle assessment of a product's environmental impact and facilitate transparency. Our EPDs conform to international standards and are 3rd party verified by ThinkStep and Underwriters Laboratory.



ACCESS | WOOD, STONE & ABSTRACT PRODUCT AVAILABILITY

Product Name	Product Code	Surface Finish	Design Type	Micro-beveled Edges	5.91" x 39.37" (150.1 mm x 1000 mm)	17.7" x 17.7" (449.6 mm x 449.6 mm)
Ashdown Plum	SX5W8000	Tick	Wood	•	•	
Black Walnut	SX5W2534	Tick	Wood	•	•	
Bleached Elm	SX5W2516	Tick	Wood	•	•	
Dusky Walnut	SX5W2542	Tick	Wood	•	•	
Frosted Oak	SX5W5020	Rustic	Wood	•	•	
Shadow Oak	SX5W5022	Rustic	Wood	•	•	
Shibori Jasmine	SX5W7800	Tick	Wood	•	•	
Simple Beech	SX5W5023	Tick	Wood	•	•	
Traditional Oak	SX5W2514	Tick	Wood	•	•	
Winter Oak	SX5W5021	Rustic	Wood	•	•	
Ceramic Dark	SX5S3566	Ceramic	Stone	•		•
Ceramic Ecu	SX5S3592	Ceramic	Stone	•		•
Ceramic Flint	SX5S2594	Ceramic	Stone	•		•
Ceramic Light	SX5S1565	Ceramic	Stone	•		•
Dry Stone Clay	SX5S4435	Ceramic	Stone	•		•
Linear Stone Black	SX5S2405	Ceramic	Stone	•		•
Linear Stone Shale	SX5S3606	Ceramic	Stone	•		•
Equator Wave	SX5AEQ39	Ceramic	Abstract	•		•
Linen Weave	SX5A3800	Ceramic	Abstract	•		•
Urban Line Felt	SX5A3271	Ceramic	Abstract	•		•

SPECIFICATIONS - ACCESS

	CONSTRUCTION	LVT with micro-beveled edges
	AVAILABLE SIZES	5.91" x 39.37" (150.1 mm x 1000 mm) 17.7" x 17.7" (449.6 mm x 449.6 mm)
	OVERALL THICKNESS	0.197" (5 mm)
	WEAR LAYER THICKNESS	20 mil
	COVERAGE PER CARTON	19.38 sq. ft. (1.8 m ²) - 5.91" x 39.37"; 21.79 sq. ft. (2.024 m ²) - 17.7" x 17.7"
	PIECES PER CARTON	12 pcs - 5.91" x 39.37", 10 pcs - 17.7" x 17.7"
	3RD PARTY CERTIFICATIONS	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)
	COMMERCIAL WARRANTY	This product is backed by our Limited 10 Year Commercial Warranty.
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
STATIC LOAD LIMIT		750 PSI
SPECIFICATION (ASTM F1700)		Class 3, Type B
HEAT STABILITY (ASTM F1514)		Passes
STAIN & CHEMICAL STABILITY (ASTM F925)		Passes
HUD/FHA REQUIREMENTS		Exceeds
AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)		Meets or exceeds ADA Guidelines
COEFFICIENT OF FRICTION (COF)		≥ 0.5 Leather; 0.6 Rubber
FLOORING RADIANT PANEL (ASTM E648)		≥ 0.45 WATTS/CM ² , Passes (Class 1)
N.B.S. SMOKE CHAMBER (ASTM E662)		< 450, Passes
INSTALLATION ADHESIVE		<p>Loose lay with perimeter glue/ Recommended adhesives: Amtico Tackifier / RH 75%, MVER 5, pH 7-10, XpressStep Spray Adhesive / RH 90%, MVER 8, pH 11, XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH 12.</p> <p>Fully Adhered: Releasable / Amtico Tackifier / RH 75%, MVER 5, pH 7-10/ Full Spread Porous & Non-Porous Subfloor.</p> <p>Fully Adhered: Permanent: Amtico 373 / RH 80%, MVER 5, pH 7-10 / Full Spread Porous & Non-Porous Subfloor, Amtico PS - High Moisture Adhesive/ RH 90%, MVER 8, pH 5-9 / Transitional Pressure Sensitive/ Full Spread Porous & Non-Porous Subfloor, Amtico Universal 2-Part / RH 80%, MVER 5, pH 7-10/ Full Spread Non-Porous Subfloor, XpressStep Spray Adhesive / RH 90%, MVER 8, pH 11, XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH 12.</p> <p>Note: Must use Amtico Universal 2-Part or XpressStep Adhesive under hospital beds and heavy rolling loads or where high performance is needed. Universal 2-Part Adhesive required in areas with excessive heat or cold expectation and exposure to direct sunlight or in area with topical water such shower rooms.</p>

