







PERFORMANCE AND FEATURES

	AVAILABLE SIZES	18" x 18" square edge tile, glue down 4' x 50' rolled sheet, glue down 24" x 24" interlocking tile, loose lay
WARRANTY 5 VEAR	WARRANTY	This product is backed by our Limited 5 year Commercial Warranty.

SUSTAINABILITY

• · · · · · · · · · · · · · · · · · · ·	•••••	•••••
BETTER PLANTS U.S. DEPARTMENT OF ENERGY	ENERGY LEADERSHIP	With one of the largest solar arrays in the flooring industry (3.3 acres in Salem NJ) and ambitious goals to improve energy efficiency by 25% over ten years, we have an ongoing partnership with the Department of Energy to lead manufacturing into smarter energy use, as well as to reduce related carbon emissions.
	SOLAR ARRAY	At 3.3 acres, we have one of the largest solar arrays in the flooring industry generating 1,000,000 kilowatt hours annually.
	WATER REDUCTION	Water is a precious natural resource and a key component in manufacturing. By investing in technology and a continual emphasis on efficiency and lean manufacturing, we have reduced our water use by more than 35% since 2007. We also actively help protect wetlands in the communities where we make flooring.
MADE IN THE	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in eight communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
	3RD PARTY CERTIFICATIONS	Certifications help navigate the world of green marketing claims. So we invest in ISO-14001 and environmentally preferable product certifications including NSF/ANSI-140, NSF/ANSI-332, FloorScore, and Green Label Plus. All of our products contribute to multiple LEED and Green Globe credits.
	RECYCLED CONTENT	We actively seek out waste streams that clog America's landfills, looking for innovative ways to use them in new products. On average, 15 tons per month of drywall, the construction industry's largest waste stream, finds new life in our VCT products. We also reclaim post-consumer carpet and tile from other flooring companies, as well as tires, telephone books, automotive glass, and other waste streams that contribute to landfills, incorporating them into carpet and hard surface flooring.

	PURPLE MARTINS	In the mid-1980s, we began attracting migrating birds called Purple Martins to our New Jersey manufacturing campus as a more natural alternative to the use of pesticides. This "Purple Martin Project" has proven to be an incredibly environmentally friendly and cost effective way to control insects. Our employees are engaged in the banding and tracking of the birds.
	HONEYBEES	In 2009, as part of an effort to show how an industrial enterprise can co-exist with the agricultural & farming community and positively contribute to both, Mannington's New Jersey corporate site began to house honeybees. We now have 5 hives in Salem, NJ and 4 in Eustis, FL. The honeybees are thriving and each year we are able to enjoy and share the honey produced.
	ISO 14001	ISO 14001 is a global environmental standard that provides a system for continual improvement in environmental performance.
C	CLIMATE REGISTRY	Mannington is dedicated to reducing our greenhouse gas emissions by 25% over 10 years. Since 2007, a 10% reduction can be attributed to energy efficiencies, process efficiencies, and use of renewable energy. Additional information can be found on theclimateregistry.org.







SPECIFICATIONS

• • • • • • • • • • • • • • • • • • • •	•	
Ø _o	CONSTRUCTION	Recycled rubber sheet goods and tiles, homogeneous throughout, with or without EPDM colored chips.
	AVAILABLE SIZES	18" x 18" square edge tile, glue down (457.2 mm x 457.2 mm) 4' x 50' rolled sheet, glue down (1,219.2 mm x 15,240 mm) 24" x 24" interlocking tile, loose lay (609.6 mm x 609.6 mm)
х	OVERALL THICKNESS	Nominal 3/8" (9.0 mm)
	PACKAGE COUNT	Individual piece/roll — minimums apply
Ō	AVERAGE WEIGHT PER PIECE	18" x 18" square edge tile: 4.37 lbs (1.98 kg) 4' x 50' rolled sheet rubber: 400 lbs (181.47 kg) 24" x 24" interlocking tile: 8 lbs (3.63 kg)
	RAPIDLY RENEWABLE RESOURCE CONTENT	Black tones contain a minimum of 91% post-consumer recycled content by total product weight. All other colors in Reset contain a minimum of 72% post-consumer and a minimum of 4% pre-consumer recycled content by total product weight.
	3RD PARTY CERTIFICATIONS	FloorScore
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
WARRANTY 5 YEAR	WARRANTY	This product is backed by our Limited 5 year Commercial Warranty.
STATIC LOAD LIMIT		400 PSI
HARDNESS (ASTM E-2240)		60 Shore A
COEFFICIENT OF FRICTION (ASTM E-2047)		≥ 0.8
FLAMMABILITY (ASTM D-2859)		Passes
SOUND TRANSMISSION COEFFICIENT (ASTM E-413)		> 50
INSTALLATION ADHESIVE		Mannington MR-710 One-Part Urethane or MR-725 Two-Part Urethane. Note: Adhesives are for 18″ x 18″ tile and sheet only. No adhesive needed for the 24″ x 24″ interlocking tile.

Floor design copyrighted by Mannington Mills, Inc. 2014. For complete specifications, visit www.manningtoncommercial.com.

Visual color variations can occur from roll to roll or tile to tile. This is not considered a manufacturing defect and does not affect product performance. Refer to Mannington's installation and maintenance instructions for best appearance results. This product is intended solely for use indoors and is not recommended or sold for any other purpose.





