



















Antique Oak II Natural 5604R Antique Oak II Tamarind 5605R





Antique Oak II Pecan 5602R Antique Oak II Date 5606R





Antique Oak II Nutmeg 5601R Antique Oak II Smoky 5607R





Southern Oak II Cotton 5615R Southern Oak II Winchester 5613R





Southern Oak II Antique 5611R Southern Oak II Rich Oak 5614R





Southern Oak II Honeytone 5612R Southern Oak II Traditional 5616R





Maple Grove IIPine 5627RMaple Grove IISaddle 5622R





Maple Grove IIHoney 5624RMaple Grove IICherry 5625R





Maple Grove IITeak 5623RMaple Grove IICreek 5628R





Maple CreekNorway 5691RMaple CreekPaperbark 5694R





Maple CreekHornwood 5692RMaple CreekHarewood 5695R





Maple CreekDrummond 5693RMaple CreekSycamore 5696R





**Persian Walnut** 







Myrrh 5674R

Jasmine 5673R

Alder 5681R English Walnut **English Walnut** Filbert 5682R

Balsam 5671R Persian Walnut



Wild Cherry Amber 5647R Wild Cherry Brighton 5648R





## Success Is in Our Science

Introducing Quantum Guard Elite, the patent-pending technology that provides the complete performance solution for heterogeneous sheet flooring.

- Engineered for ease of cleaning and reduced maintenance costs
- Highest abrasion resistance in the industry
- · Advanced stain resistance
- Excellent slip resistance

## **Cleans Better Than Competitors**

Quantum Guard Elite

**Leading Competitor** 





Advanced urethane chemistry and an optimized texture make resilient sheet with Quantum Guard Elite easy to clean. (Results after 10 passes with a wet microfiber mop on soiled floor.)

#### **Best-in Class Abrasion Resistance**

Quantum Guard Elite

**Leading Competitor** 





Our proprietary blend of aluminum oxide particles is suspended evenly through the urethane top coat, giving the industry's best abrasion resistance. (Results after 50 passes with sanding block.)

## **Stain Resistance That Endures**

Quantum Guard Elite

Leading Competitor





With new protective compounds from the aerospace industry and dentistry, Quantum Guard Elite's stain resistance performs over time at the same high level as the day it was installed. (Results after 1,000 passes with a sanding block, staining with a blue Sharpie and cleaning with an alcohol wipe.)

## Warranted to Work

Products with Quantum Guard Elite feature our Limited Quantum Guard Elite Wear Warranty and Limited Commercial Warranty.



# Fresh aesthetics, engineered to perform.

Realities II brings natural beauty to high-performance heterogeneous sheet flooring. The collection features Quantum Guard® Elite technology and a new texture to provide exceptional ease of cleaning, reduced maintenance costs and long-term durability. The eight patterns include woods and a wood-hybrid, offered in a variety of plank widths and 48 colors in total. With a range of traditional, transitional and modern wood visuals, Realities II delivers unsurpassed performance and sophisticated style to all types of environments.





#### Realities II® Collection

Style Antique Oak II, Boardwalk, English Walnut, Maple Creek, Maple Grove II,

Persian Walnut, Southern Oak II, Wild Cherry

Construction Heterogeneous Sheet (Non-ortho phthalate construction)

Classification ASTM F1303 Type I, Grade 1, Class B

Total Thickness 0.080" (2.03 mm)

Wear Layer Thickness 0.020" (0.51 mm)

Wear Layer Quantum Guard Elite®

Width 6' (1.83 m), 9' (2.75 m), 12' (3.66 m)

Colors 6 each style

Pattern Repeat 36" L x 72" W - Boardwalk, English Walnut, Maple Creek, Persian Walnut, Wild Cherry

48" L x 48" W - Maple Grove II, Southern Oak II

48" L x 72" W - Antique Oak II

Packaging
6' - 30-50 yd² (25.0-41.8 m²)

9' - 30-75 yd² (25.0-62.7 m²) 12' - 30-100 yd² (25.0-83.6 m²) 47 lbs/yd² (2.55 kg/m²)

Weight 4.7 lbs/yd² (2.55 kg/m²)

Adhesive Porous & Non-porous Substrates:

V-88 Full Spread, Transitional Pressure Sensitive, High Moisture

V-95 Full Spread, 2-part Epoxy

XpressStep for LVT & Sheet Vinyl Full Coverage Spray

Porous Substrates Only: V-82 Full Spread, Acrylic Base

 $\textbf{Note:} \ \textbf{Must} \ \textbf{use} \ \textbf{V-95} \ \textbf{or} \ \textbf{XpressStep} \ \textbf{adhesive} \ \textbf{under} \ \textbf{hospital} \ \textbf{beds} \ \textbf{and} \ \textbf{heavy} \ \textbf{rolling} \ \textbf{load} \ \textbf{areas.} \ \textbf{Use} \ \textbf{V-95} \ \ \textbf{in} \ \textbf{Operating} \ \textbf{Rooms} \ \textbf{or} \ \textbf{or} \ \textbf{volume} \ \textbf{or} \ \textbf{volume} \ \textbf{volume} \ \textbf{volume} \ \textbf{or} \ \textbf{or} \ \textbf{volume} \ \textbf{volume} \ \textbf{or} \ \textbf{or} \ \textbf{volume} \ \textbf{or} \ \textbf{or} \ \textbf{volume} \ \textbf{or} \ \textbf{or}$ 

where higher risk of topical moisture would be a concern.

QuickStix® Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring.

QuickStix® floors can be used immediately after installation, even in extreme moisture areas.

 ${\bf Seam\ Method} \\ {\bf Mannington\ Commercial\ Weld\ Rods\ or\ MLG-33\ Chemical\ Seam\ Sealer.\ Mannington\ Seam\ Coater\ Pen\ for\ high\ Mannington\ Seam\ Coater\ Pen\ for\ high\ Mannington\ Seam\ Sealer.\ Mannington\ Seam\ Seam\ Sealer.\ Mannington\ Seam\ Sealer.\ Mannington\ Seam\ Sealer.\ Mannington\ Seam\ Seale$ 

traffic areas. Note: Heat welding is the recommended procedure for healthcare and high traffic applications.

#### Testing

HUD/FHA Meets / Exceeds

ADAG (American Disability Act Guidelines) Passes

 Flexibility (ASTM F790)
 Passes - 1/4" Mandrel - No Crack/Break

 Static Load (ASTM F970)
 Passes - Residual Indent ≤ 0.005"

 Static Load (ASTM F970 mod.)
 Passes - 2,000 PSI; Residual Indent ≤ 0.005"

 Rolling Resistance/Caster Chair (ISO 4918)
 25,000 Cycles, No Significant Change

Short Term Residual Indentation (ASTM F1914/F1303) Passes - Must be ≤ 0.012"

Flooring Radiant Panel (ASTM E648) Passes - Class 1; ≥ 0.45 watts/cm<sup>2</sup>

Smoke Density (ASTM E662) Passes - ≤ 450

Slip Resistance (ASTM C1028, Dry)

Passes - ≥ 0.5 Leather; 0.6 Rubber

Acoustic IIC (ASTM E492)

Acoustic STC (ASTM E90)

Resistance to Light (ASTM F1515)

Passes - < 8 Delta E Color Change

Chemical Resistance (ASTM F925)

Resistance to Heat (ASTM F1514)

Passes - < 8 Delta E Color Change

Resistance to Mold/Mildew (ASTM G21/E2180)

Passes - No More Than Slight Change

#### **Environmental Data**

mindful MATERIALS

Indoor Air Quality FloorScore Certified; CDPH v1.1-2010

Product Declarations EPD

LEED Scoreboard May contribute to LEED credits:

LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring

LEED v4: Building Product Disclosure & Optimization - EPDs; IEQc2 - Low Emitting Materials Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information

Manufacturing Salem, NJ (USA) - ISO 14001 EMS Registered

Warranty

Limited 10 Year Commercial Warranty

Limited 10 Year Quantum Guard Elite® Wear Warranty