

SPACIA FIRST | WOOD, ABSTRACT & STONE
SPACIA FIRST 20 | WOOD





**COVER: STONE - Dry Stone Alba SF3S4401, ABSTRACT - Steel SF3A2804, WOOD - White Oak SF3W2548, SP5W2548
ABOVE: ABSTRACT - Linen Weave SF3A3800**



ABSTRACT - Bronze SF3A4805

ABSTRACT - Steel SF3A2804



STONE - Dry Stone Loam SF3S4434

STONE - Dry Stone Cinder SF3S4433



STONE - Desert Sandstone SF3S4607

STONE - Dry Stone Alba SF3S4401



WOOD - Honey Oak SF3W2504, SP5W2504



WOOD - Warm Maple SF3W2502, SP5W2502









WOOD - Dry Cedar SF3W2535, SP5W2535

WOOD - White Oak SF3W2548, SP5W2548


PERFORMANCE AND FEATURES

	<p>AVAILABLE SIZES</p>	<p>12" x 12" (305 x 305 mm), 12" x 24" (305 x 610 mm), 18" x 18" (457 x 457 mm), 6" x 36" (152 x 915 mm), 7.25" x 48" (185 x 1220 mm) All with micro-beveled edges. Sizes are style dependent.</p>
	<p>WARRANTY</p>	<p>Spacia First is backed by our Limited 10 Year Light Commercial Warranty. Spacia First 20 is backed by our Limited 10 Year Commercial Warranty.</p>

SUSTAINABILITY

	<p>ENERGY LEADERSHIP</p>	<p>With one of the largest solar arrays in the flooring industry (3.3 acres in Salem NJ) and ambitious goals to improve energy efficiency by 25% over ten years, we have an ongoing partnership with the Department of Energy to lead manufacturing into smarter energy use, as well as to reduce related carbon emissions.</p>
	<p>WATER REDUCTION</p>	<p>Water is a precious natural resource and a key component in manufacturing. By investing in technology and a continual emphasis on efficiency and lean manufacturing, we have reduced our water use by 30% company-wide since 2007. We also actively help protect wetlands in the communities where we make flooring.</p>
	<p>SOLAR ARRAY</p>	<p>At 3.3 acres, we have one of the largest solar arrays in the flooring industry, generating 1,000,000 kilowatt hours annually.</p>
	<p>US MANUFACTURING</p>	<p>Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.</p>
	<p>ISO 14001</p>	<p>ISO 14001 is a global environmental standard that provides a system for continual improvement in environmental performance.</p>
	<p>3RD PARTY CERTIFICATIONS</p>	<p>Certifications help navigate the world of green marketing claims. So we invest in ISO-14001 and environmentally preferable product certifications including NSF/ANSI-140, NSF/ANSI-332, FloorScore, and Green Label Plus. All of our products may contribute to multiple LEED and Green Globe credits.</p>

SUSTAINABILITY

	<p>PURPLE MARTINS</p>	<p>In the mid-1980s, we began attracting migrating birds called Purple Martins to our New Jersey manufacturing campus as a more natural alternative to the use of pesticides. This “Purple Martin Project” has proven to be an incredibly environmentally friendly and cost effective way to control insects. Our employees are engaged in the banding and tracking of the birds.</p>
	<p>HONEYBEES</p>	<p>In 2009, as part of an effort to show how an industrial enterprise can co-exist with the agricultural & farming community and positively contribute to both, Mannington’s New Jersey corporate site began to house honeybees, and now have 5 hives in Salem, NJ and 4 in Eustis, FL. The honeybees are thriving and each year we are able to enjoy and share the honey we produce.</p>
	<p>CE MARK</p>	<p>Certifies that a product has met EU health, safety, and environmental requirements, which ensure consumer safety. Manufacturers in the European Union (EU) and abroad must meet CE marking requirements where applicable in order to market their products in Europe.</p>
	<p>CLIMATE REGISTRY</p>	<p>Mannington is dedicated to reducing our greenhouse gas emissions by 25% over 10 years. Since 2007, a 10% reduction can be attributed to energy efficiencies, process efficiencies, and use of renewable energy. Additional information can be found on theclimateregistry.org.</p>
	<p>ENVIRONMENTAL PRODUCT DECLARATION</p>	<p>EPDs communicate the comprehensive life cycle assessment of a product’s environmental impact and facilitate transparency. Our EPDs conform to international standards and are 3rd party verified by ThinkStep and Underwriters Laboratory.</p>



SPACIA FIRST | WOOD, STONE & ABSTRACT PRODUCT AVAILABILITY
SPACIA FIRST 20 | WOOD PRODUCT AVAILABILITY

	Product Name	PSpacia First Product Code	Spacia First 20 Product Code	Collection	Price Point	Surface Finish	Micro-beveled Edges	6" x 36" (152 x 915 mm)	7.25" x 48" (185 x 1220 mm)	12" x 12" (305 x 305 mm)	12" x 24" (305 x 610 mm)	12" x 24" (305 x 610 mm) Cross Grain	18" x 18" (457 x 457 mm)
WOOD	Bitter Walnut	SF3W2492	SP5W2492	Wood	Standard	Tick	•	•					
	Deep Cherry	SF3W3020	SP5W3020	Wood	Standard	Tick	•	•					
	Dry Cedar	SF3W2535	SP5W2535	Wood	Standard	Barnwood	•	•					
	English Oak	SF3W2498	SP5W2498	Wood	Standard	Tick	•	•					
	Frosted Oak	SF3W5020	SP5W5020	Wood	Standard	Barnwood	•		•				
	Honey Oak	SF3W2504	SP5W2504	Wood	Standard	Tick	•	•					
	Natural Oak	SF3W3021	SP5W3021	Wood	Standard	Tick	•	•					
	Pale Ash	SF3W2518	SP5W2518	Wood	Standard	Tick	•	•					
	Rich Walnut	SF3W2494	SP5W2494	Wood	Standard	Tick	•	•					
	Shadow Oak	SF3W5022	SP5W5022	Wood	Standard	Barnwood	•		•				
	Smoked Grey Oak	SF3W3023	SP5W3023	Wood	Standard	Tick	•	•					
	Tudor Oak	SF3W2495	SP5W2495	Wood	Standard	Tick	•	•					
	Warm Maple	SF3W2502	SP5W2502	Wood	Standard	Tick	•	•					
	White Oak	SF3W2548	SP5W2548	Wood	Standard	Tick	•	•					
STONE	Ceramic Ecru	SF3S3592		Stone	Standard	Ceramic	•						•
	Desert Sandstone	SF3S4607		Stone	Standard	Ceramic	•					•	
	Dry Stone Alba	SF3S4401		Stone	Standard	Deep Ceramic	•			•			
	Dry Stone Cinder	SF3S4433		Stone	Standard	Deep Ceramic	•						•
	Dry Stone Loam	SF3S4434		Stone	Standard	Deep Ceramic	•						•
	Linear Stone Shale	SF3S3606		Stone	Standard	Ceramic	•				•		
	Sift Stone Canvas	SF3S6133		Stone	Standard	Deep Ceramic	•			•			
ABSTRACT	Bronze	SF3A4805		Abstract	Standard	Ceramic	•				•		
	Linen Weave	SF3A3800		Abstract	Standard	Ceramic	•						•
	Steel	SF3A2804		Abstract	Standard	Ceramic	•				•		

SPECIFICATIONS

	SPACIA FIRST	SPACIA FIRST 20
 CONSTRUCTION	LVT with micro-beveled edges	
 AVAILABLE SIZES	12" x 12" (305 x 305 mm), 12" x 24" (305 x 610 mm), 18" x 18" (457 x 457 mm), 6" x 36" (152 x 915 mm), 7.25" x 48" (185 x 1220 mm). Sizes are style dependent.	6" x 36" (152 x 915 mm) and 7.25" x 48" (185 x 1220 mm). Sizes are style dependent.
 WEAR LAYER THICKNESS	12 mil	20 mil
 OVERALL THICKNESS	0.08" (2.0 mm)	0.098" (2.5 mm)
 COVERAGE PER CARTON	27 sq. ft. of 12" x 12"; 38 sq. ft. of 12" x 24"; 27 sq. ft. of 18" x 18"; 27 sq. ft. of 6" x 36"; 21.75 sq. ft. of 7.25" x 48"	27 sq. ft. of 6" x 36"; 21.75 sq. ft. of 7.25" x 48"
 PIECES PER CARTON	27 pcs - 12" x 12"; 19 pcs - 12" x 24"; 12 pcs - 18" x 18"; 18 pcs - 6" x 36"; 9 pcs - 7.25" x 48"	
 3RD PARTY CERTIFICATIONS	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)	
 LEED	Mannington Commercial products may contribute to multiple LEED credits.	
 WARRANTY	Spacia First is backed by our Limited 10 Year Light Commercial Warranty. Spacia First 20 is backed by our Limited 10 Year Commercial Warranty.	
STATIC LOAD LIMIT	750 PSI	
SPECIFICATION (ASTM F1700)	Class 3, Type B	
HEAT STABILITY (ASTM F1514)	Passes	
STAIN & CHEMICAL STABILITY (ASTM F925)	Passes	
HUD/FHA REQUIREMENTS	Exceeds	
AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)	Meets or exceeds ADA Guidelines	
COEFFICIENT OF FRICTION (COF)	≥ 0.5 Leather; 0.6 Rubber	
FLOORING RADIANT PANEL (ASTM E648)	Passes - Class 1	
N.B.S. SMOKE CHAMBER (ASTM E662)	< 450, Passes	
INSTALLATION ADHESIVE	Amtico 373 / Full Spread Porous & Non-Porous Subfloor, Amtico PS - High Moisture Adhesive / Transitional Pressure Sensitive/ Full Spread Porous & Non-Porous Subfloor, Amtico Universal 2-Part/ Full Spread Non-Porous Subfloor, XpressStep Spray Adhesive / RH 90%, MVER 8, pH 11, XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH 12. Note: Must use Amtico Universal 2-Part or XpressStep Adhesive under hospital beds and heavy rolling loads or where high performance is needed.	

