

**SPECIFICATIONS | AMTICO 30 - CONNECTED**

	<b>CONSTRUCTION</b>	LVT with micro-beveled edges
	<b>AVAILABLE SIZES</b>	9" x 18" (228.3 x 457.5 mm) Fade 18" x 18" (457.5 x 457.5 mm) Grid 1.5" X 18" (38.1 x 457.5 mm) Accent with micro-beveled edges
	<b>WEAR LAYER THICKNESS</b>	30 mil (0.76 mm)
	<b>OVERALL THICKNESS</b>	0.098" (2.5mm)
	<b>PIECES PER CARTON</b>	20 pcs - 18" x 18"; 40 pcs - 9" x 18"; 60 pcs - 1.5" x 18"
	<b>COVERAGE PER CARTON</b>	45 sq. ft. (4.18 m2) - 18" x 18"; 45 sq. ft. (4.18 m2) - 9" x 18"; 11.25 sq. ft. (1.045 m2) - 1.5" x 18"
	<b>WARRANTY</b>	This product is backed by our Limited 15 Year Commercial Warranty and Limited 15 Year Quantum Guard® HP Wear Warranty.
	<b>QUANTUM GUARD® HP</b>	The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention and slip retardance when compared to standard LVT floors - resulting in 70% annual savings in maintenance costs.
	<b>3RD PARTY CERTIFICATIONS</b>	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)
	<b>LEED</b>	Mannington Commercial products may contribute to multiple LEED credits.
	<b>RAPIDLY RENEWABLE CONTENT</b>	Contains 3% rapidly renewable resource content.
	<b>US MANUFACTURING</b>	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
	<b>LOOP®</b>	Mannington's next closed-loop recycling program, we are reclaiming and recycling end-of-life LVT into new LVT. This further extends our ability to keep post-consumer LVT out of landfills and reducing the environmental impact of our products. Contact your local Mannington representative, or call 800.241.2262.
	<b>STATIC LOAD LIMIT</b>	750 PSI
	<b>SPECIFICATIONS (ASTM F1700)</b>	Class III, Type B
	<b>HEAT STABILITY (ASTM F1514)</b>	Passes
	<b>STAIN &amp; CHEMICAL STABILITY (ASTM F925)</b>	Passes
	<b>HUD/FHA REQUIREMENTS</b>	Exceeds
	<b>AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)</b>	Meets or exceeds ADA Guidelines
	<b>COEFFICIENT OF FRICTION (COF)</b>	≥ 0.5 Leather; 0.6 Rubber
	<b>FLOORING RADIANT PANEL (ASTM E648)</b>	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
	<b>N.B.S. SMOKE CHAMBER (ASTM E662)</b>	< 450-Passes
	<b>INSTALLATION ADHESIVE</b>	Porous & Non-Porous Substrates: Amtico High Pressure Sensitive, Full Spread / RH 90%, MVER 8, pH5-9; Amtico 373, Full Spread / RH 80%, MVER 5, pH 7-10; XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11; XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH12. Non-Porous Substrates or where higher performance is required: Amtico Universal, Full Spread, 2 Part Urethane / RH 80%, MVER 5, pH 7-10. Under Hospital Beds and Heavy Rolling Loads: Amtico Universal, Full Spread, 2 Part Urethane / RH 80%, MVER 5, pH 7-10; XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11; XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH12.

20846\_CONNECTED

