

PHYSICAL CONSTRUCTION

Construction	Recycled Rubber Sheet Goods and Tiles, Homogeneous Throughout, With or Without EPDM Colored Chips	
Size	18" x 18" Square Edge Tile, Glue Down (457.2 mm x 457.2 mm) 4' x 50' Rolled Sheet, Glue Down (1,219.2 mm x 15,240 mm) 24" x 24" Interlocking Tile, Loose Lay (609.6 mm x 609.6 mm)	
Overall Thickness	3/8" (9.0 mm)	
Packaging	18" x 18" Square Edge Tile:	Sold by the piece
	4' x 50' Rolled Sheet Rubber:	Sold by full roll only
	24" x 24" Interlocking Tile:	Sold by the piece
Weight Per Piece	18" x 18" Square Edge Tile:	4.37 Lbs. (1.98 kg)
	4' x 50' Rolled Sheet Rubber:	400 Lbs. (181.47 kg)
	24" x 24" Interlocking Tile:	8 Lbs. (3.63 kg)
Static Load Limit	400 psi	

ENVIRONMENTAL

Recycled Content	Black = 91% Post-Consumer / Colors = 72% Post-Consumer
FloorScore Indoor Air Quality	SCS Certified
Manufacture Location	Lancaster, PA USA

TESTING

Density (ASTM D-3676)	≥ 60 lbs./ft. ³ (961 kf/m ³)
Static Coefficient of Friction (ASTM D2047)	≥ 0.8
Chemical Resistance (ASTMF-925)	No Change
Hardness (ASTM E-2240)	60 Shore A
Sound Transmission Coefficient (ASTM E-413)	> 50
Flammability (ASTM D-2859)	Passes

WARRANTY

Warranty	Limited 5 Year Commercial Warranty
----------	------------------------------------

INSTALLATION

Installation Adhesive	Mannington MR-710 One-Part Urethane or MR-725 Two-Part Urethane
	Note: Adhesives are for 18 x 18 tile and sheet only. No adhesive is needed for the 24 x 24 interlocking tile.

- Visual color variations can occur from roll to roll or tile to tile. This is not considered a manufacturing defect and does not affect product performance. Refer to Mannington's installation and maintenance instructions for best appearance results.
- Reset is not recommended in commercial areas that require static dissipation.
- Perform subfloor moisture test ASTM F-1869 Calcium Chloride Test or ASTM F-2170 % RH and a bond test as described in Mannington's Installation Guide to determine if surfaces are dry, free of curing and hardening compounds, old adhesive, and other coatings.
- In the spaces to receive rubber flooring and accessories, maintain a minimum temperature of 65° F (18° C) and a maximum temperature of 85° F (29°C) for at least 48 hours before, during, and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55° F (13° C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.