

MANNINGTON COMMERCIAL

LEGACY HAND-CRAFTED HARDWOOD COLLECTION

Construction	Engineered 5-Ply Premium Hardwood with cross-grain construction
Top Face	Rotary cut top face
Wear Layer	Quantum Guard™ HP 8-Step UV cured urethane aluminum oxide finish
Gloss Level	Low Luster
Edge Finish	Full-Bevel
Plank Widths	5" (127 mm)
Plank Thickness	1/2" (12.7 mm)
Square Feet per carton	31.35
Weight per carton	48
Cartons per pallet	36
Origin	Made in USA – Lacey Compliant – FSC Pure Option available for orders over 10,000 sq. ft. Contact your Mannington representative for further information
HUD/FHA Requirements	Meets or Exceeds
Coefficient of Friction (ASTM-D-2394)	Exceeds ADA Guidelines of .60
Flooring Radiant Panel Test (ASTM-E-648) \geq .45 watts/cm², Passes (Class I)	
Flame Spread Tunnel Test (ASTM E-84)	Meets Class C, Flame spread
Sound Transmission class STC (ASTM E-90)	≥ 50
Impact Insulation Class IIC (ASTM E-492, E989)	≥ 50
Installation Method	Glue, Nail, Staple or Floating
Installation Adhesive	Glue Method requires Mannington's Ultra Spread EZ Adhesive
Underlayment	Floating method requires Mannington Whisper 3N1 underlayment and MegaGlue™ adhesive
Subfloor Requirements	Above, On or Below Grade
Trim and Molding	Color coordinating pre-finished: reducer strip, step nosing, baby threshold, t-molding, wall base and quarter round. Each are 84" (2.4m) long with 5 pieces per carton.

Limited 5 Year Quantum Guard™ HP Finish Warranty. Limited Lifetime Pre-installation, Structure and Subfloor Bond Warranty.

Custom color matching is available on selected skus, with a 10,000 square foot production minimum. Up charges will apply. Allow 3-4 weeks for sample delivery from receipt of swatch and custom color form. Allow 4-6 week lead time for production from date of customer approval.

Wood products contain natural variations in grain and color. It is recommended to order several samples when making final product selection.

Ordinary sweeping and mopping is usually sufficient to keep the floor clean. If needed, an occasional cleaning with UltraClean™ or equivalent is recommended. Never flood the floor with water. Do not use soap-based detergents, as these may leave a dull finish on the floor. Do not use abrasive cleaners, steel wool, or scouring powder, as these may dull the floor. Dirt, wetness, and improper maintenance may cause significant variation in actual performance. Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance. This product is intended solely for use as an indoor covering and is not recommended or sold for any other purpose. Use entryways systems outside each entrance to prevent dirt, and other substrates from being tracked onto floor

dn May2016