Mannington COMMERCIAL

Style	Interval Modular (Non-Ortho Phthalate)	Interweave Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	30% Post Production Nylon 70% Type 6,6 Nylon	50% Post Production Nylon 50% Type 6,6 Nylon
Dye Method	Yarn/Solution	Yarn/Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	8.66 (34.09 per 10 cm)	11 (43.31 per 10 cm)
Density	5,236 (194.56 kg/m³)	5,785 (214.96 kg/m³)
Pile Thickness	0.110" (2.79 mm)	0.112" (2.84 mm)
Weight	16 oz/yd² (542 g/m²)	18 oz/yd² (610 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular
Sizes	24" x 24'' (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	1	1
Packaging	6.22 yd² / 14 Tiles	6.22 yd² / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar	Horizontal Brick Ashlar, Quarter Turn

Testing	
Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	3.5

Environmental Data	
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified

Warranty	
	Limited Lifetime Wear & Backing Warranty Limited 15 Year XGUARD® Stain Resistant Warranty Limited 15 Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com

Style	Knit Modular (Non-Ortho Phthalate)	Link Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	50% Post Production Nylon 50% Type 6,6 Nylon	50% Post Production Nylon 50% Type 6,6 Nylon
Dye Method	Yarn/Solution	Yarn/Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10.83 (42.64 per 10 cm)	11.16 (43.94 per 10 cm)
Density	5,700 (211.80 kg/m³)	5,944 (220.87 kg/m³)
Pile Thickness	0.120" (3.05 mm)	0.109" (2.77 mm)
Weight	19 oz/yd² (644 g/m²)	18 oz/yd² (610 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular
Sizes	24" x 24'' (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	1	1
Packaging	6.22 yd² / 14 Tiles	6.22 yd² / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar, Quarter Turn	Horizontal Brick Ashlar

Testing	
Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	Knit Modular - 4, Link Modular - 3.5

Environmental Data	
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified

Warranty	
	Limited Lifetime Wear & Backing Warranty Limited 15 Year XGUARD® Stain Resistant Warranty Limited 15 Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with Purpose

Style	Loop Modular (Non-Ortho Phthalate)	Stringworks II Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	50% Post Production Nylon 50% Type 6,6 Nylon	100% Post Production Nylon
Dye Method	Yarn/Solution	Yarn/Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10.66 (41.97 per 10 cm)	13.16 (51.81 per 10 cm)
Density	5,355 (198.98 kg/m³)	7,000 (260.11 kg/m³)
Pile Thickness	0.121" (3.07 mm)	0.108" (2.74 mm)
Weight	18 oz/yd² (610 g/m²)	21 oz/yd² (712 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular
Sizes	24" x 24'' (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	1	1
Packaging	6.22 yd² / 14 Tiles	6.22 yd² / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar, Quarter Turn	Horizontal Brick Ashlar, Quarter Turn

Testing	
Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	3.5

Environmental Data	
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified

Warranty	
	Limited Lifetime Wear & Backing Warranty Limited 15 Year XGUARD® Stain Resistant Warranty Limited 15 Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com