

PHYSICAL CONSTRUCTION

Construction	Homogeneous Thermoset Rubber with smooth profile design containing rapidly renewable resource content
Size (Roll)	4' x 49.2' (1.2M x 15 M+) Full rolls only
Size (Tile)	24" x 24" (610 mm x 610 mm) (Min. Order 3,520 SF for 24" Tile)
Overall Thickness	.118 "(3 mm) sheet and tile
Roll Size	196.8 sq. ft. min. (18.5m ²)
Pieces Per Carton	20
Weight Per Carton	24" x 24" - 76 lbs. per carton
Static Load Limit	1200 psi

ENVIRONMENTAL

FloorScore Indoor Air Quality	SCS Certified
Rapidly Renewable Resource Content	8% Rapidly Renewable resource content by total product weight

TESTING

HUD / FHA requirements	Exceeds
ASTM Specification (F-1859) - Sheet	Type 1 – Homogeneous Rubber Sheet
ASTM Specification (F-1344) – Tile	Class 1, Type B, Grade 1
Static Coefficient of Friction	Meets or Exceeds ADA Guidelines for walking surfaces and ramps
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm ² , Passes (Class I)
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 – Passes
Bacteria Resistance (ASTM G-21):	Resistant to bacteria & micro-organism activity
Bacteria Resistance (ASTM E-2180):	Resistant to bacteria & micro-organism activity

WARRANTY

Warranty - Sheet	Limited 5 Year Wear Warranty; Limited 10 Year Commercial Warranty
Warranty - Tile	Limited 5 Year Wear Warranty; Limited 10 Year Commercial Warranty

INSTALLATION

Installation Adhesive	MR-911 Acrylic Adhesive MR-721 Epoxy Adhesive MR-725 Polyurethane Adhesive
Chemical Seam Sealer	Not Available – Heat Weld Only
Heat Weld Seaming	Mannington ColorFields Solid Weld Rods

ColorFields formulations are made with our superior rubber so they retain their amazing color, resist indentations and cracking, and are quiet underfoot. Requires no finish or stripping, lowering maintenance costs.

ColorFields is not recommended in areas that require static dissipation or where exposure to animal fats or cooking oils will occur.

Dirt, wetness and improper maintenance may cause significant variation in actual performance. Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance. Can be installed in wet areas when seams are properly sealed and perimeter edges are protected and covered up the wall. This product is intended solely for use indoors and is not recommended or sold for any other purpose.

Use entryway systems outside each entrance to prevent dirt, sand, grit and other substance from being tracked onto floor.