

Style	Wood	Abstract, Stone
Construction	Luxury Vinyl Tile Non-ortho Phthalate	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B
Total Thickness	0.08" (2.0 mm)	0.08" (2.0 mm)
Wear Layer Thickness	12 mil (0.30 mm)	12 mil (0.30 mm)
Wear Layer	Enhanced Urethane	Enhanced Urethane
Edge Treatment	Micro-bevel	Micro-bevel
Sizes	6" x 36" (152 x 915 mm) 7.25" x 48" (184 x 1219 mm) Sizes are style dependent; refer to Product Availability Chart	12" x 12" (305 x 305 mm) 12" x 24" (305 x 610 mm) 18" x 18" (457 x 457 mm) Sizes are style dependent; refer to Product Availability Chart
Colors	14	3 - Abstract, 7 - Stone
Packaging	6" x 36" - 18 pcs, 27 ft ² (2.508 m ²), 19.74 lbs (8.954 kg) 7.25" x 48" - 9 pcs, 21.75 ft ² (2.021 m ²), 15.9 lbs (7.212 kg)	12" x 12" - 27 pcs, 27 ft ² (2.508 m ²), 20.12 lbs (9.13 kg) 12" x 24" - 19 pcs, 38 ft ² (3.53 m ²), 27.78 lbs (12.6 kg) 18" x 18" - 12 pcs, 27 ft ² (2.508 m ²), 20.12 lbs (9.13 kg)
Adhesive	Amtico PSA Full Spread, Transitional Pressure Sensitive, High Moisture Amtico RP-18 Full Spread, One Component XpressStep for LVT Full Coverage Spray XpressStep Premium for LVT Full Coverage High Moisture Spray Porous Substrates Only: Amtico 373 Full Spread <small>Note: Must use Amtico RP-18, XpressStep or XpressStep Premium adhesive under hospital beds and heavy rolls load areas. Use Amtico RP-18 where high higher risk of topical moisture would be a concern.</small>	
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.	
Testing		
HUD/FHA	Passes	
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break	
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft	
Squareness (ASTM F540)	Passes - Max 0.010"	
Static Load (ASTM F970 mod.)	Passes - 1,000 PSI; Residual Indent ≤ 0.005"	
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Resistance to Light (ASTM F1515)	Passes	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
Product Declarations	EPD	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; IIEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information	
Manufacturing	China	
Warranty		
Limited 10 Year Light Commercial Warranty		