

PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Patterned Loop (Non-Ortho Phthalate Construction) ECONYL (100% regenerated Type 6 Nylon) Solution 1/12 9 .091 inches 14 Ounces Per Square Yard Average Density = 5,538; Weight Density = 77,538 100% Synthetic Infinity Modular Reinforced Composite Closed Cell Polymer 24" X 24" Modular Tiles Shuffled or Horizontal Brick Ashlar
FACE FIBER:	
DYE METHOD:	
GAUGE:	
STITCHES PER INCH:	
PILE THICKNESS:	
TUFTED YARN WEIGHT:	
DENSITY:	
PRIMARY BACKING:	
SECONDARY BACKING:	
STANDARD SIZE:	
INSTALLATION METHOD:	

ENVIRONMENTAL:

RECYCLED CONTENT:	Contains Pre-Consumer Recycled Content*
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Gold
CRI GREEN LABEL PLUS ID:	GLP7616
3 rd Party Certified Product Specific Type III EPD	

WARRANTIES:

WARRANTY:	Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection
BLEACH RESISTANT WARRANTY:	ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
DIMENSIONAL STABILITY AACHEN TEST:	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

RECOMMENDED ADHESIVE:

RELEASEABLE ADHESIVE:	Mannington Infinity Pressure Sensitive Adhesive
CRI GREEN LABEL PLUS ID:	GLP70522
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.