

Style	BurkeBase Type TS 1/8" *	BurkeBase Type TP 1/8" ** (Non-Ortho Phthalate)
Construction	Thermoset Rubber	Thermoplastic Rubber
Finish	Satin	Matte
Classification	ASTM F1861 Type TS, Group 1	ASTM F1861 Type TP, Group 1
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Coved or Toeless 2.5" (64 mm) 4" (102 mm) 6" (152 mm) 10" (254 mm) Toeless Only	Coved or Toeless 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm)
Colors	95 (36 are Accord)	100 (36 are Accord)
Packaging	25-4' pieces = 100' per carton Toeless 10" = 15-4' pieces	1-100' continuous roll or 25-4' pieces
Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10"	Coved = 27/39/53 lbs. Toeless = 24/39/50 lbs. Toeless 10" = 51 lbs.	Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs.
Weight Per Carton – Corners	Coved = 3/4/7 lbs. Toeless = 3/4/7 lbs. Toeless 1/8" = 3/4/9 lbs.	Coved = 3/4/9 lbs. Coved = 3/4/9 lbs.
Corners (must be ordered at time of wall base order to ensure color match)	Factory molded corners available	Factory pre-formed corners available
Adhesive	Burke BR-101	Burke BR-101
<b>Testing</b>		
Flexibility (ASTM F137)	Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.	
Flammability (ASTM E-84)	Class B rating with smoke density of 150 - 200	
Heat Resistance (ASTM E648)	Passes, Class I, .45 watts/cm <sup>2</sup>	
Smoke Generation (ASTM E662)	Maximum Specific Optical Density of 450 or less	
<b>Environmental Data</b>		
Indoor Air Quality	FloorScore Certified	
LEED Scoreboard	May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials	
Manufacturing	Calhoun, GA USA	
<b>Warranty</b>		
	Limited 5 Year Commercial Warranty	

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

\* Type TS Coved and Toeless 4' lengths available in 2.5', 4', 6', and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523, 597, 701 and 727 in 4" height only.

\*\* Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5', 4', 4.5', and 6" heights. Both available in .080 & 1/8" thickness.

Style	BurkeBase Type TV 1/8" ** (Non-Ortho Phthalate)	BurkeBase Type TV .080" ** (Non-Ortho Phthalate)
Construction	Vinyl	Vinyl
Finish	Matte	Matte
Classification	ASTM F1861 Type TV, Group 1	ASTM F1861 Type TV, Group 1
Total Thickness	1/8" (3.2 mm)	.080" (2.0 mm) & 1/8" (3.2 mm)
Profile	Coved or Toeless	Coved or Toeless
Sizes	2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm)	2.5" (64 mm) 4" (102 mm) 6" (152 mm)
Colors	100 (36 are Accord)	100 (36 are Accord)
Packaging	1-100' continuous roll or 25-4' pieces	1-100' continuous roll or 25-4' pieces
Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10"	Coved (1/8") = 24/37/41/53 lbs. Toeless (1/8") = 23/36/41/52 lbs.	Coved (.080") = 19/27/41/42 lbs. Toeless (.080") = 17/25/41/39 lbs.
Weight Per Carton – Corners	Coved = 3/4/9 lbs. Toeless = 3/4/9 lbs.	Coved (.080") = 3/3/8 lbs. Toeless (.080") = 2/3/7 lbs.
Corners (must be ordered at time of wall base order to ensure color match)	Factory pre-formed corners available	Factory pre-formed corners available
Adhesive	Burke BR-101	Burke BR-101
<b>Testing</b>		
Flexibility (ASTM F137)	Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.	
Static Load ASTM F910	500 psi	
Flammability ASTM E648	.45 watts/cm², Passes (Class I)	
Slip Resistance ASTM C1028	<450 – Passes	
<b>Environmental Data</b>		
Indoor Air Quality	FloorScore Certified	
LEED Scoreboard	May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials	
Manufacturing	Calhoun, GA (USA)	
<b>Warranty</b>		
	Limited 5 Year Commercial Warranty	Limited 5 Year Commercial Warranty

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

\* Type TS Coved and Toeless 4' lengths available in 2.5', 4', 6', and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523 and 597 in 4" height only.

\*\* Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5', 4', 4.5", and 6" heights. Both available in .080 & 1/8" thickness.