

PHYSICAL CONSTRUCTION:

CONSTRUCTION:

Pattern Loop

(Non-Ortho Phthalate Construction)

FACE FIBER:

Invista Antron Lumena Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5

DYE METHOD:

Solution

GAUGE:

5/64

STITCHES PER INCH:

10.66

PILE THICKNESS:

.108 Inches

TUFTED YARN WEIGHT:

20 Ounces Per Square Yard

DENSITY:

Average Density = 6,667; Weight Density = 133,334

PRIMARY BACKING:

100% Synthetic

SECONDARY BACKING:

Infinity Modular Reinforced Composite Closed Cell Polymer

STANDARD SIZE:

24" X 24" Modular Tiles

INSTALLATION METHOD:

Horizontal Brick Ashlar

ENVIRONMENTAL:

RECYCLED CONTENT:

Contains Pre-Consumer Recycled Content*

MANUFACTURE LOCATION:

Calhoun, Georgia 30701 USA

NSF / ANSI-140 CERTIFICATION:

Gold

CRI GREEN LABEL PLUS CERTIFIED

ISO 14001 CERTIFIED

3RD PARTY CERTIFICATION:

Type III EPD (Environmental Product Declaration)

V2.1 HPD (Health Product Declaration)

WARRANTIES:

WARRANTY:

Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection

BLEACH RESISTANT WARRANTY:

ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills

STAIN RESISTANT WARRANTY:

XGUARD with 15 Year Limited Warranty Against Staining

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648):

Class I (Direct Glue)

SMOKE CHAMBER (ASTM E-662):

Less than 450 (Flaming Mode)

METHENAMINE PILL TEST (ASTM D-2859):

Passes

DIMENSIONAL STABILITY AACHEN TEST:

Passes

ELECTROSTATIC PROPENSITY (AATCC 134):

Less than 3.0 KV

RECOMMENDED ADHESIVE:

RELEASEABLE ADHESIVE:

Mannington Infinity Pressure Sensitive Adhesive

CRI GREEN LABEL PLUS ID:

GLP70522

VOC LIMITS:

Meets SCAQMD Rule #1168

BOND WARRANTY:

Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.