

Style	Wood	Stone & Abstract
Construction	Polymeric Composite Flooring	Polymeric Composite Flooring
Classification	Commercial	Commercial
Total Thickness	0.098" (2.5 mm)	0.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.51 mm)	20 mil (0.51 mm)
Wear Layer	Quantum Guard® HP	Quantum Guard® HP
Edge Treatment	Micro-bevel	Micro-bevel
Sizes	4.5" x 36" (114 x 915 mm) 7.25" x 48" (184 x 1219 mm) Sizes are style dependent; refer to Product Availability Chart	12" x 24" (305 x 610 mm) 18" x 18" (457 x 457 mm) Sizes are style dependent; refer to Product Availability Chart
Colors	16	2 each style
Packaging	4.5" x 36" - 40 pcs, 45 ft ² (4.18 m ²), 27.8 lbs (12.61 kg) 7.25" x 48" - 19 pcs, 45.81 ft ² (4.26 m ²), 28.37 lbs (12.87 kg)	12" x 24" - 23 pcs, 46 ft ² (4.27 m ²), 28.42 lbs (12.89 kg) 18" x 18" - 20 pcs, 45 ft ² (4.18 m ²), 27.8 lbs (12.61 kg)
Adhesive	Porous & Non-Porous Substrates: Amtico PSA Full Spread, Transitional Pressure Sensitive, High Moisture Amtico RP-18 Full Spread, One Component Porous Substrates Only: Amtico 373 Full Spread Note: Must use Amtico RP-18 adhesive under hospital beds and heavy rolling load areas. Use Universal where higher risk of topical moisture would be a concern.	
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.	
Testing		
HUD/FHA	Passes	
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break	
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft	
Squareness (ASTM F540)	Passes - Max 0.010"	
Static Load (ASTM F970 mod.)	Passes - 1,500 PSI; Residual Indent ≤ 0.005"	
Residual Indentation (ASTM F3261)	Passes - < 0.007"	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Resistance to Light (ASTM F1515)	Passes	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Environmental Data		
Recycled Content	5%	
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
Product Declarations	EPD, HPD	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc4 Recycled Content, IEQ4.1 Low Emitting Adhesives, IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients IEQc2 - Low Emitting Materials	
Manufacturing	Coventry, UK	
Warranty		
	Limited 10 Year Commercial Warranty Limited 10 Year Quantum Guard® HP Wear Warranty	