










## SPECIFICATIONS | CITY PARK

	CONSTRUCTION	Solid Core construction with micro-beveled edges featuring a FloorArmor™ core and locking technology.
	AVAILABLE SIZES	5.8" x 37" nominal (148 mm x 940 mm)
	WEAR LAYER THICKNESS	20 mil (0.51 mm)
	OVERALL THICKNESS	0.236" (6 mm); FloorArmor™ Core 0.197" (5 mm); Sound Abatement Pad 0.039" (1 mm)
	PIECES PER CARTON	8 pcs
	COVERAGE PER CARTON	11.97 sq. ft.
	3RD PARTY CERTIFICATIONS	FloorScore
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
	QUANTUM GUARD® HP	The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention, and slip retardance when compared to standard LVT floors - resulting in 70% annual savings in maintenance costs.
	FLOORARMOR™	FloorArmor™ is a unique core innovation that delivers a superior combination of benefits. With industry leading commercial product specifications, FloorArmor™ delivers enhanced dimensional stability, ease of installation, superior acoustic properties and outstanding indentation resistance, combined with a product that is virtually waterproof.
	WARRANTY	This product is backed by our Limited 10 Year Commercial Warranty, Limited 10 Year No Gap Warranty, and Limited 10 Year Quantum Guard® HP Wear Warranty.
	STATIC LOAD LIMIT	750 PSI
	SPECIFICATIONS (ASTM F3261)	Class 1, Type B, Backing Class B
	HEAT STABILITY (ASTM F1514)	Passes
	STAIN & CHEMICAL RESISTANCE (ASTM F925)	Passes
	COEFFICIENT OF FRICTION (COF)	≥ 0.5 Leather; 0.6 Rubber
	FLOORING RADIANT PANEL (ASTM E648)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
	HUD/FHA REQUIREMENTS	Exceeds
	AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)	Meets or exceeds ADA Guidelines
	N.B.S. SMOKE CHAMBER (ASTM E662)	< 450, Passes
	INSTALLATION ADHESIVE	City Park utilizes a patented locking system that does not require adhesive.

