











SPECIFICATIONS | DIVERGENT

| | | |
|---|--|---|
|  | CONSTRUCTION | Luxury Vinyl Tile and Plank with bevelled edges |
| | AVAILABLE SIZES | 18" x 18" (457 x 457 mm); 18" x 36" (457 x 915 mm) Estuary only. All with beveled edges |
|  | WEARLAYER THICKNESS | 30 mil (0.76 mm) |
|  | OVERALL THICKNESS | 0.098" (2.5 mm) |
|  | PIECES PER CARTON | 18 pcs - 18" x 18"; 9 pcs - 18" x 36" |
|  | COVERAGE PER CARTON | 40.5 sq. ft. (3.76m ²) of 18" x 18" and 18" x 36" |
|  | 3RD PARTY CERTIFICATION | FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration) |
|  | LEED | Mannington Commercial products may contribute to multiple LEED credits. |
|  | QUANTUM GUARD® HP | The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wearlayer eliminates the need for polish, while enhancing durability, cleanability, appearance retention and slip retardance when compared to standard LVT floors - resulting in 70% annual savings in maintenance costs. |
|  | RAPIDLY RENEWABLE CONTENT | Contains 3% rapidly renewable resource content. |
|  | LOOP® | Mannington's next closed-loop recycling program, we are reclaiming and recycling end-of-life LVT into new LVT. This further extends our ability to keep post-consumer LVT out of landfills and reducing the environmental impact of our products. Contact your local Mannington representative, or call 800.241.2262 |
|  | US MANUFACTURING | Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in eight communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products. |
|  | WARRANTY | This product is backed by our Limited 15 Year Commercial Warranty and Limited 15 Year Quantum Guard® HP Wear Warranty. |
|  | XPRESS | When you really need it now. Our innovative delivery program ensures that you get the carpet and hard surface products you need quickly and reliably. With product available to ship within 5 business days, Mannington's xpress program leads the industry in service. Please refer to www.manningtoncommercial.com to view xpress products. |
| | STATIC LOAD LIMIT | 750 PSI |
| | SPECIFICATIONS (ASTM F-1700) | Class III, Type B |
| | HEAT STABILITY (ASTM F-1514) | Passes |
| | STAIN & CHEMICAL RESISTANCE (ASTM F-925) | Passes |
| | COEFFICIENT OF FRICTION (COF) | ≥ 0.5 Leather; 0.6 Rubber |
| | FLOORING RADIANT PANEL (ASTM-E-648) | ≥ 0.45 watts/cm ² , Passes (Class 1) |
| | N.B.S. SMOKE CHAMBER (ASTM-E-662) | <450-Passes |
| | IMPACT SOUND TRANSMISSION (I1C) (ASTM-E-492) | N/A |
| | INSTALLATION ADHESIVE | Porous Substrate: V-82 Full Spread Non-Porous Substrate: V-95 Full Spread, 2 Part Epoxy Porous & Non-Porous Substrate: M-Guard V-88 Full Spread, Transitional Pressure Sensitive, High Moisture or XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11, XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH12 Note: Must use V-95 or XpressStep for LVT or Premium Spray adhesive under hospital beds and heavy rolling loads or where high performance is needed. |