

Product Specifications
ENFORCER
Skate & Spike Resistant Rubber Sports Tile

MANNINGTON
COMMERCIAL

PHYSICAL CONSTRUCTION

Construction	Thermoset Rubber Tile
Size	36" x 36" (914.4 mm x 914.4 mm)
Profile – ColorScape	Sculptured
Profile – ColorSpec	Sculptured
Overall Thickness	.236" (6.00 mm)
Pieces Per Carton	Sold by the piece
Weight Per Carton	18 lbs. (39.6 kgs) per carton
Static Load Limit	500 psi

ENVIRONMENTAL

FloorScore Indoor Air Quality	SCS Certified
Manufacture Location	San Jose, CA USA

TESTING

ASTM Specification (F-1344)	Class 1-A (ColorScape) and Class 1-B (ColorSpec), both with the exception of Durometer (hardness) which will be 70 +/- 10
Static Coefficient of Friction	Meets or Exceeds ADA Guidelines for walking surfaces and ramps
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm ² , Passes (Class I)
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 – Passes

WARRANTY

Warranty	Limited 10 Year Wear Warranty; Limited 10 Year Commercial Warranty
----------	--

INSTALLATION

Installation Adhesive	Mannington MR-721 Epoxy Adhesive M-725 Polyurethane Adhesive
-----------------------	---

Mannington Enforcer Skate and Spike Resistant Rubber Sports Tile is available in ColorScape and ColorSpec colorways. Enforcer is made specifically to resist sports-shoe spike and skate traffic. Skate guards are not required. Enforcer is made with our superior rubber so it retains color depth, resists indentations and punctures, and is quiet underfoot. Built-in waxes produce a natural luster that requires no finishes, top coatings, or waxes. This eliminates stripping, which dramatically lowers maintenance costs.

- Enforcer is not recommended in commercial areas that require static dissipation.
- In the spaces to receive rubber flooring and accessories, maintain a minimum temperature of 65° F (18° C) and a maximum temperature of 85° F (29°C) for at least 48 hours before, during, and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55° F (13° C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substance from being tracked onto floor.

Choices That Work

800 241 2262 manningtoncommercial.com