

PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Patterned Loop (Non-Ortho Phthalate Construction)
FACE FIBER:	Invista Antron Legacy Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5
DYE METHOD:	Solution / Yarn
GAUGE:	5/64
STITCHES PER INCH:	10.5
PILE THICKNESS:	.108 inches
TUFTED YARN WEIGHT:	21 Ounces Per Square Yard
DENSITY:	Average Density = 7,000; Weight Density = 147,000
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	Integra HP with Chemically Weldable Seams for Complete Moisture Barrier
STANDARD SIZE:	12' 6" Width
PATTERN REPEAT:	18 3/4" W x 29 1/2" L

ENVIRONMENTAL:

RECYCLED CONTENT:	Contains Recycled Content*
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Gold
CRI GREEN LABEL PLUS ID:	GLP7616
3 rd Party Certified Product Specific Type III EPD	

WARRANTIES:

WARRANTY:	Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Wick-Back, Delamination, Tuft Bind, Unraveling, and Static Protection
BLEACH RESISTANT WARRANTY:	ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM-E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

RECOMMENDED ADHESIVE:

PERMANENT ADHESIVE:	Mannington Integra-2 Adhesive
CRI GREEN LABEL PLUS ID:	GLP07281
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Integra HP Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.