Mannington COMMERCIAL

Belvedere V Collection

Style	Belvedere V Broadloom	Belvedere V Modular (Non-Ortho Phthalate)
Construction	Solid Color Cut Pile	Solid Color Cut Pile
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Piece Dyed	Piece Dyed
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	13.33 (42.64 per 10 cm)	13.33 (42.64 per 10 cm)
Density	5,837 (231.20 kg/m^3)	5,837 (231.20 kg/m^3)
Pile Thickness	0.222″ (2.06 mm)	0.222″ (2.06 mm)
Weight	36 oz/yd^2 (475 g/m^2)	36 oz/yd^2 (475 g/m^2)
Backing Type	UltraBac® RE, Integra HP®	Infinity® 2 Modular
Sizes	12′ (3.66 m)	24″ x 24″ (45.72 x 91.44 cm)
Colors	27	27
Packaging	N/A	6.22 yd^2 / 14 Tiles
Adhesive	Ultra Adhesive Integra-2 Adhesive	Infinity® Adhesive
Installation Method	N/A	Monolithic

Testing	
Dimensional Stability (AACHEN Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm^2
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D-2859)	Passes

Environmental Data	
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, UltraBac® RE - Platinum, Integra HP® - Gold
Recycled Content	Contains Recycled Content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified

Warranty	
	Limited Lifetime Wear & Backing Warranty Limited 15 Year XGUARD® Stain Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.