



SPECIFICATIONS - COLOR ANCHOR | ARC

| | | |
|---|---|---|
|  | CONSTRUCTION | Heterogeneous Sheet (Non-ortho phthalate construction) |
|  | AVAILABLE SIZES | Available in 6' (1.83 m), 9' (2.75 m), 12' (3.66 m) |
|  | WEAR LAYER THICKNESS | .020" (.51 mm) |
|  | OVERALL THICKNESS | .080" (2.03 mm) |
|  | SQUARE YARD PER ROLL (MIN-MAX) | 6': 30 – 50 sq. yds. (25.0 – 41.8 sq. m.) 9': 30 – 75 sq. yds. (25.0 – 62.7 sq. m.) 12': 30 – 100 sq. yds. (25.0 – 83.6 sq. m.) |
|  | QUANTUM GUARD® ELITE | A patent-pending technology, Quantum Guard® Elite is engineered for ease of cleaning and provides industry-leading abrasion resistance, advanced stain resistance and excellent slip resistance. |
|  | WARRANTY | This product is backed by our Limited 10 Year Commercial Warranty and Limited 10 Year Quantum Guard® Elite Wear Warranty. |
|  | 3RD PARTY CERTIFICATIONS | FloorScore, Industry-wide 3rd Party Type III EPD (Environmental Product Declaration) |
| | LEED | Mannington Commercial products may contribute to multiple LEED credits. |
|  | US MANUFACTURING | Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products. |
| | PATTERN REPEAT | 36" L x 72" W |
| | STATIC LOAD LIMIT | 750 PSI |
| | SPECIFICATION (ASTM F1303) | Type 1, Grade 1, Class B |
| | HUD/FHA REQUIREMENTS | Exceeds |
| | AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG) | Meets or Exceeds ADA Guidelines |
| | COEFFICIENT OF FRICTION (COF) | ≥ 0.5 Leather; 0.6 Rubber |
| | FLOORING RADIANT PANEL (ASTM E648) | ≥ .45 watts / cm2, Passes – Class 1 |
| | N.B.S. SMOKE CHAMBER (ASTM E662) | < 450-Passes |
| | INSTALLATION ADHESIVE | Porous and Non-Porous Substrates: V-88 - 8lbs. MVER (ASTM F1869) / 90% RH (ASTM F2170) Full Spread, Transitional Pressure Sensitive, High Moisture Porous and Non-Porous Substrates: XpressStep for Sheet Vinyl - 8lbs MVER (ASTM F1869 / 90% RH (ASTM F2170) Spray Full Coverage, High Moisture Porous and Non-Porous Substrates: V-95 -3lbs. MVER (ASTM F1869) / 75% RH (ASTM F2170) Full Spread 2-part Epoxy Porous Substrates: V-82 - 3lbs. MVER (ASTM F1869) / 75% RH (ASTM F2170) Full Spread Note: Must use V-95 or XpressStep for Sheet adhesive under hospital beds and heavy rolling load areas. Use V-95 where higher risk of topical moisture would be a concern. |
| | SEAM METHOD | Mannington Commercial Weld Rods or MLG-33 Chemical Seam Sealer Mannington Seam Coater Pen for high traffic areas. Note: Heat welding is the recommended procedure for healthcare and high traffic applications. |

For complete specifications, visit our website, manningtoncommercial.com.

*Visual / Color variations can occur from roll to roll. This variation does not affect product performance.



MANNINGTON
COMMERCIAL