Product Specifications

BELVEDERE V 42 – ULTRABAC RE (40 Yard Minimum)

MANNINGTON COMMERCIAL

PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Solid Color Cut Pile
FACE FIBER:	Type 6,6 Nylon
DYE METHOD:	Piece Dyed
GAUGE:	1/10
STITCHES PER INCH:	11.6
PILE THICKNESS:	.270 Inches
TUFT DENSITY:	116
TUFTED YARN WEIGHT:	42 Ounces Per Square Yard
DENSITY:	Average Density = 5,600; Weight Density = 235,200
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	UltraBac RE with Minimum 10% Recycled Content and Lifetime Warranty
STANDARD SIZE:	12’ Width
PATTERN REPEAT:	None

ENVIRONMENTAL:

RECYCLED CONTENT:	Minimum 10% Post-Consumer Recycled Content by Total Product Weight
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Platinum
CRI GREEN LABEL PLUS ID:	GLP0678

WARRANTIES:

WARRANTY:	Lifetime Limited Warranty, Covering Face Wear, Delamination, Tuft Bind, Unraveling, and Static Protection

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM-E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

RECOMMENDED ADHESIVE:

MULTI-PURPOSE ADHESIVE:	Mannington Ultra Adhesive
CRI GREEN LABEL PLUS ID:	GLP70513
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	10 Year Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.