

SPECIFICATIONS – NATURE'S PATHS

	CONSTRUCTION	LVT with micro-beveled edges
	AVAILABLE SIZES	18" x 18" (457.2 mm x 457.2 mm); 18" x 36" (457.2 mm x 914.4 mm); 4" x 36" (101.5 mm x 914.4 mm) VIA only
	WEAR LAYER THICKNESS	20 mil (0.51 mm)
	OVERALL THICKNESS	.100" (2.5 mm)
	PIECES PER CARTON	18 per carton - 18" x 18"; 9 per carton - 18" x 36"; 36 per carton - 4" x 36" VIA only
	COVERAGE PER CARTON	40.5 sq. ft. - 18" x 18" and 18" x 36" / 36 sq. ft. - 4" x 36" VIA only
	WEIGHT PER CARTON	38.1 lbs (17.3 Kg) per carton - 18" x 18" and 18" x 36" 33.8 lbs (15.3 Kg) per carton - 4" x 36" VIA only
	QUANTUM GUARD® HP	The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention and slip retardance when compared to standard LVT floors - resulting in 70% annual savings in maintenance costs.
	WARRANTY	This product is backed by our Limited 10 Year Commercial Warranty and Limited 10 Year Quantum Guard® HP Wear Warranty.
	QUICKSTIX	LVT with pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix floors can be used immediately after installation, even in extreme moisture areas.
	3RD PARTY CERTIFICATIONS	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)
	RAPIDLY RENEWABLE CONTENT	Contains 3% rapidly renewable resource content.
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
	LOOP®	Mannington's next closed-loop recycling program, we are reclaiming and recycling end-of-life LVT into new LVT. This further extends our ability to keep post-consumer LVT out of landfills and reducing the environmental impact of our products. Contact your local Mannington representative, or call 800.241.2262.
	XPRESS	When you really need it now. Our innovative delivery program ensures that you get the carpet and hard surface products you need quickly and reliably. With product available to ship within 5 business days, Mannington's Xpress program leads the industry in service. Please refer to www.manningtoncommercial.com to view Xpress products.
STATIC LOAD LIMIT		750 PSI
SPECIFICATIONS (ASTM F1700)		Class 3, Type B
HEAT STABILITY (ASTM F1514)		Passes
STAIN & CHEMICAL STABILITY (ASTM F925)		Passes
HUD/FHA REQUIREMENTS		Exceeds
AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAAG)		Meets or exceeds ADA Guidelines
COEFFICIENT OF FRICTION (COF)		≥ 0.5 Leather; 0.6 Rubber
FLOORING RADIANT PANEL (ASTM E648)		≥ 0.45 watts/cm2, Passes (Class 1)
N.B.S. SMOKE CHAMBER (ASTM E662)		450-Passes
INSTALLATION ADHESIVE		Porous Substrate: V-82 Full Spread Non-Porous Substrate: V-95 Full Spread, 2 Part Epoxy QuickStix pre-applied adhesive / 99% RH, MVER 18, pH12. Porous & Non-Porous Substrate: M-Guard V-88 Full Spread, Transitional Pressure Sensitive, High Moisture or XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11, XpressStep Premium Spray Adhesive / RH 93%, MVER 18, pH12 Note: Must use V-95 or XpressStep for LVT or Premium Spray adhesive under hospital beds and heavy rolling loads or where high performance is needed.

