

Style	Ecliptic Point Broadloom	Ecliptic Point Modular (Non-Ortho Phthalate)	Light Grid Broadloom
Construction	Textured Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon
Dye Method	Yarn	Yarn	Yarn
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	6.33 (24.92 per 10 cm)	6.33 (24.92 per 10 cm)	6.5 (26.89 per 10 cm)
Density	6,603 (255.94 kg/m ³)	6,603 (255.94 kg/m ³)	6,888 (255.94 kg/m ³)
Pile Thickness	0.169" (4.29 mm)	0.169" (4.29 mm)	0.162" (4.11 mm)
Weight	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)
Backing Type	UltraBac® RE	Infinity® 2 Modular	UltraBac® RE
Size	12' (3.66 m)	24" x 24" (60.96 x 60.96 cm)	12' (3.66 m)
Colors	13	13	13
Pattern Repeat	24" W x 15 1/2" L (60.96 x 39.37 cm)	N/A	24" W x 43" L (60.96 x 109.22 cm)
Packaging	N/A	6.22 yd ² / 14 Tiles	N/A
Adhesive	Ultra Adhesive	Infinity® Adhesive	Ultra Adhesive
Installation Method	N/A	Vertical Ashlar	N/A

Testing

Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	3.5

Environmental Data

NSF/ANSI 140 Certification	UltraBac® RE - Platinum, Infinity® 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered

Warranty

Limited Lifetime Wear & Backing
 Limited 15 Year XGUARD® Stain Resistant
 Limited 15 Year ColorSafe® Bleach Resistant

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com

Style	Light Grid Modular (Non-Ortho Phthalate)	Shadow Play Broadloom	Shadow Play Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon	Ultron Type 6, 6 Nylon
Dye Method	Yarn	Yarn	Yarn
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	6.83 (26.89 per 10 cm)	6.5 (25.59 per 10 cm)	6.5 (25.59 per 10 cm)
Density	6,888 (255.94 kg/m ³)	6,340 (235.58 kg/m ³)	6,340 (235.58 kg/m ³)
Pile Thickness	0.162" (4.11 mm)	0.176" (4.47 mm)	0.176" (4.47 mm)
Weight	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)	31 oz/yd ² (1,051 g/m ²)
Backing Type	Infinity [®] 2 Modular	UltraBac [®] RE	Infinity [®] 2 Modular
Size	24" x 24" (60.96 x 60.96 cm)	12' (3.66 m)	24" x 24" (60.96 x 60.96 cm)
Colors	13	13	13
Pattern Repeat	N/A	24" W x 79 1/2" L (60.96 x 201.93 cm)	N/A
Packaging	6.22 yd ² / 14 Tiles	N/A	6.22 yd ² / 14 Tiles
Adhesive	Infinity [®] Adhesive	Ultra Adhesive	Infinity [®] Adhesive
Installation Method	Horizontal Brick Ashlar	N/A	Monolithic

Testing

Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	3.5

Environmental Data

NSF/ANSI 140 Certification	UltraBac [®] RE - Platinum, Infinity [®] 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered

Warranty

Limited Lifetime Wear & Backing
 Limited 15 Year XGUARD[®] Stain Resistant
 Limited 15 Year ColorSafe[®] Bleach Resistant

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with Purpose