










## SPECIFICATIONS- Edge Effects

	CONSTRUCTION	Co-Extruded Thermoplastic Rubber, Type TP
	AVAILABLE SIZES	12' (3.65 m), 25' (7.62 m), 36' (11 m), 50' (15.24 m) Profile dependent
	OVERALL THICKNESS	3/16" (4.76 mm), 1/4" (6.35 mm), 5/16" (7.94 mm), 3/8" (9.52 mm), 1/2" (12.7 mm) Profile dependent
	PACKAGE COUNT	1 per carton
	AVERAGE WEIGHT	23-48 lbs (10.43-21.80 kgs) per carton Profile dependent
	3RD PARTY CERTIFICATIONS	FloorScore
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
	WARRANTY	This product is backed by our Limited 5 Year Commercial Warranty.
FINISH		Smooth Matte
CORNERS		Pre-mitered inside and outside corners
CORNERS PER CARTON		10
CORNER WEIGHT PER CARTON		5 - 7 lbs (2.27 kgs - 3.18 kgs) Profile dependent
SPECIFICATION (ASTM F-1861)		Type TP, Group 1
FLOORING RADIANT PANEL TEST (ASTM-E-648)		≥ .45 watts/cm <sup>2</sup> , Passes - Class 1
N.B.S. SMOKE CHAMBER TEST (ASTM-E-662)		< 450, Passes
INSTALLATION ADHESIVE		Mannington MR-101, Acrylic Wall Base Adhesive

Floor designs copyrighted by Mannington Mills, Inc 2014. For complete specifications, visit [www.manningtoncommercial.com](http://www.manningtoncommercial.com).



**MANNINGTON**  
COMMERCIAL