

PHYSICAL CONSTRUCTION

Construction	Thermoset Rubber Tiles
Size	18 1/8" x 18 1/8" (460 mm x 460 mm)
Profile – ColorScape	Round, Square & Sculptured (Face profile height for round and square is .025" / 6 mm)
Profile – ColorSpec	Square and Sculptured (Face profile height for square is .025" / 6 mm)
Overall Thickness	1/8" (3.175 mm)
Pieces Per Carton	20 pieces
Weight Per Carton	44 lbs. (20 kgs) per carton
Static Load Limit	500 psi

ENVIRONMENTAL

Contains 4% Rapidly Renewable Resource Content by total product weight

3rd Party Certified Industry-wide Type III EPD

FloorScore Indoor Air Quality SCS Certified – CA01350

Manufacture Location San Jose, CA USA

TESTING

ASTM Specification (F-1344)	Class 1, Type A (Colorscape) Class 1, Type B (Colorspec)
Static Coefficient of Friction	Meets or Exceeds ADA Guidelines at .60
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm ² , Passes (Class I)
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 – Passes

WARRANTY

Warranty Limited 10 Year Wear Warranty; Limited 10 Year Commercial Warranty

INSTALLATION

Installation Adhesives	Mannington MR-721 Epoxy Adhesive M-725 Polyurethane Adhesive MR-911 One Part Acrylic Adhesive for above-grade and stairwell applications
------------------------	--

ColorScape and ColorSpec formulations are made with our superior rubber so they retain their amazing color, resist indentations and cracking, and are quiet underfoot. Built-in waxes produce a natural luster that requires no finish or stripping, lowering maintenance costs.

- ColorScape and ColorSpec are not recommended in commercial areas that require static dissipation.
- In the spaces to receive rubber flooring and accessories, maintain a minimum temperature of 65° F (18° C) and a maximum temperature of 85° F (29° C) for at least 48 hours before, during, and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55° F (13° C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substance from being tracked onto floor.