

Style	Wood
Construction	Luxury Vinyl Tile
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.51 mm)
Wear Layer	Enhanced Urethane
Edge Treatment	Micro-bevel
Sizes	6" x 36" (152 x 915 mm)
Colors	8
Packaging	24 pcs, 36 ft <sup>2</sup> (3.345 m <sup>2</sup> ), 23.29 lbs. (10.56 kg)
Adhesive	<b>Porous and Non-porous Substrates:</b> <b>V-95</b> Full Spread, 2-part Epoxy <b>V-88</b> Full Spread, Transitional Pressure Sensitive, High Moisture <b>XpressStep</b> for LVT & Sheet Vinyl Full Coverage Spray <b>XpressStep Premium</b> for LVT Full Coverage High Moisture Spray <b>Porous Substrates Only:</b> <b>V-82</b> Full Spread  <b>Note:</b> Must use V-95, XpressStep or XpressStep Premium under hospital beds and heavy rolling load areas. Use V-95 where higher risk of topical moisture would be a concern.
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance.
Testing	
HUD/FHA	Passes
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes - 1,500 PSI; Residual Indent ≤ 0.005"
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes
Environmental Data	
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, <a href="http://mindfulmaterials.origin.build">mindfulmaterials.origin.build</a> , for current transparency information
Manufacturing	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered
Warranty	Limited 10 Year Commercial Warranty

## Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit [manningtoncommercial.com](http://manningtoncommercial.com)