











SPECIFICATIONS / INSIGHT PLUS GB

	CONSTRUCTION	Heterogeneous Light Commercial Sheet (Non-Phthalate Construction)
	AVAILABLE SIZES	6' (1.83 m) and 12' (3.66 m)
	OVERALL THICKNESS	0.080 inches (2.03 mm)
	WEAR LAYER THICKNESS	Insight Plus GB - .014" (.36mm)
	WEIGHT PER SQUARE YARD	3.3 lbs/yd ² (1.77 kg/m ²)
	SQUARE YARD PER ROLL (MIN-MAX)	6' - 35 - 70 sq. yds. (29.3 - 58.5 sq. m.) 12' - 35 - 170 sq. yds. (29.3 - 142.5 sq. m.)
	3RD PARTY CERTIFICATIONS	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)
	WARRANTY	This product is backed by our Limited 10 Year Light Commercial Warranty and Limited 10 Year Quantum Guard® HP Wear Warranty.
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
PATTERN REPEAT		Pattern dependent - see our website, www.mannington.com for details
STATIC LOAD LIMIT		125 PSI
SPECIFICATION (ASTM F1303)		Type I, Grade 2, Class C
HUD/FHA REQUIREMENTS		Exceeds
COEFFICIENT OF FRICTION (COF)		Meets or exceeds ADA Guidelines (≥0.6)
FLOORING RADIANT PANEL (ASTM E648)		≥ 0.45 Watts/cm ² , Passes - Class 1
N.B.S. SMOKE CHAMBER (ASTM E662)		< 450, Passes
INSTALLATION ADHESIVE		MT-711
SEAM METHOD		MLG-33 Urethane Sealer

Floor designs copyrighted by Mannington Mills, Inc 2014. For complete specifications, visit manningtoncommercial.com.

*Visual /Color variations can occur from roll to roll. This variation does not affect product performance.



MANNINGTON
COMMERCIAL