

Style	Fan Fold Broadloom	Fan Fold Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Antron® Lumena™ Type 6,6 Nylon	Antron® Lumena™ Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	9.33 (36.73 per 10 cm)	9.33 (36.73 per 10 cm)
Density	6,171 (229.30 kg/m ³)	6,171 (229.30 kg/m ³)
Pile Thickness	0.140" (3.56 mm)	0.140" (3.56 mm)
Weight	24 oz/yd ² (814 g/m ²)	24 oz/yd ² (814 g/m ²)
Backing Type	UltraBac® RE	Infinity® 2 Modular
Sizes	12'6" (3.81 m)	24" x 24" (60.96 x 60.96 cm)
Colors	12	12
Pattern Repeat	18.75" W x 25.75" L (47.625 x 65.405 cm)	N/A
Packaging	N/A	6.22 yd ² / 14 Tiles
Adhesive	Mannington Ultra Adhesive	Infinity® Adhesive
Installation Method	N/A	Horizontal Brick Ashlar, Monolithic, Vertical Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5	
Environmental Data		
NSF/ANSI 140 Certification	UltraBac® RE - Platinum, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	EPD, HPD	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty	
	Limited 15 Year XGUARD® Stain Resistant Warranty	
	Limited 15 Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com

Style	Mountain Fold Modular (Non-Ortho Phthalate)	Valley Fold Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Antron® Lumena™ Type 6,6 Nylon	Antron® Lumena™ Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	8.83 (34.76 per 10 cm)	9.16 (36.06 per 10 cm)
Density	6,171 (229.30 kg/m ³)	6,171 (229.30 kg/m ³)
Pile Thickness	0.140" (3.56 mm)	0.140" (4.70 mm)
Weight	24 oz/yd ² (814 g/m ²)	24 oz/yd ² (814 g/m ²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular
Sizes	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	12	12
Pattern Repeat	N/A	N/A
Packaging	6.22 yd ² / 14 Tiles	6.22 yd ² / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar, Monolithic, Vertical Ashlar	Horizontal Brick Ashlar, Monolithic, Vertical Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5	
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	EPD, HPD	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty	
	Limited 15 Year XGUARD® Stain Resistant Warranty	
	Limited 15 Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com