

| Style | Relay Modular (Non-Ortho Phthalate) | Transmit Modular (Non-Ortho Phthalate) |
|--------------------------------------|--|--|
| Construction | Textured Patterned Loop | Textured Patterned Loop |
| Face Fiber | Antron® Lumena™ Type 6,6 Nylon | Antron® Lumena™ Type 6,6 Nylon |
| Dye Method | Solution | Solution |
| Gauge | 5/64 (50.39 per 10 cm) | 5/64 (50.39 per 10 cm) |
| Stitches Per Inch | 10 (39.37 per 10 cm) | 10 (39.37 per 10 cm) |
| Density | 6,690 (248.95 kg/m ³) | 6,690 (248.95 kg/m ³) |
| Pile Thickness | 0.113" (2.90 mm) | 0.113" (2.90 mm) |
| Weight | 21 oz/yd ² (712 g/m ²) | 21 oz/yd ² (712 g/m ²) |
| Backing Type | Infinity® Modular | Infinity® Modular |
| Size | 24" x 24" (60.96 x 60.96 cm) | 24" x 24" (60.96 x 60.96 cm) |
| Colors | 8 | 8 |
| Packaging | 6.22 yd ² / 14 Tiles | 6.22 yd ² / 14 Tiles |
| Adhesive | Infinity® Adhesive | Infinity® Adhesive |
| Installation Method | Horizontal Brick Ashlar, Vertical Ashlar, Monolithic | Horizontal Brick Ashlar, Vertical Ashlar, Monolithic |
| Testing | | |
| Dimensional Stability (AACHEN Test) | Passes | |
| Electrostatic Propensity (AATCC 134) | Less than 3.0 kV | |
| Flooring Radiant Panel (ASTM E648) | Passes - Class 1; ≥ 0.45 watts/cm ² | |
| Smoke Density (ASTM E662) | Passes - ≤ 450 | |
| Methenamine Pill Test (ASTM D2859) | Passes | |
| Hexapod (ASTM D5252) TARR Rating | 3.5 | |
| Environmental Data | | |
| NSF/ANSI-140 Certification | Infinity® 2 Modular - Gold | |
| Recycled Content | Contains recycled content | |
| Indoor Air Quality | CRI Green Label Plus Certified | |
| Recyclability | LOOP® | |
| Product Declarations | EPD, HPD | |
| LEED Scoreboard | May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials | |
| mindful MATERIALS | Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information | |
| Manufacturing | Calhoun, GA (USA) - ISO 14001 Registered | |
| Warranty | | |
| | Limited Lifetime Wear & Backing Warranty | |
| | Limited 15 Year XGUARD® Stain Resistant Warranty | |
| | Limited 15 Year ColorSafe® Bleach Resistant Warranty | |

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent, pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Crafted with purpose

For more information, contact your local Mannington representative or visit manningtoncommercial.com