

**Product Specifications**  
**ORO -- INFINITY 2 MODULAR****PHYSICAL CONSTRUCTION:**

|                      |  |
|----------------------|--|
| CONSTRUCTION:        | Patterned Loop<br>(Non-Ortho Phthalate Construction)   |
| FACE FIBER:          | Invista Antron Legacy Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5 |
| DYE METHOD:          | Solution / Yarn  |
| GAUGE:               | 5/64   |
| STITCHES PER INCH:   | 9.66   |
| PILE THICKNESS:      | .100 Inches  |
| TUFTED YARN WEIGHT:  | 21 Ounces Per Square Yard  |
| DENSITY:             | Average Density = 7,560; Weight Density = 158,760  |
| PRIMARY BACKING:     | 100% Synthetic   |
| SECONDARY BACKING:   | Infinity 2 Modular Reinforced Composite Closed Cell Polymer  |
| STANDARD SIZE:       | 24" X 24" Modular Tiles  |
| INSTALLATION METHOD: | Monolithic or Horizontal Brick Ashlar  |

**ENVIRONMENTAL:**

|                                      |  |
|--------------------------------------|--|
| RECYCLED CONTENT:                    | Contains Pre-Consumer Recycled Content   |
| MANUFACTURE LOCATION:                | Calhoun, Georgia 30701 USA   |
| NSF / ANSI-140 CERTIFICATION:        | Gold   |
| CRI GREEN LABEL PLUS CERTIFIED       |  |
| ISO 14001 CERTIFIED                  |  |
| 3 <sup>RD</sup> PARTY CERTIFICATION: | Type III EPD (Environmental Product Declaration)<br>V2.1 HPD (Health Product Declaration). |

**WARRANTIES:**

|                            |  |
|----------------------------|--|
| WARRANTY:                  | Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection |
| BLEACH RESISTANT WARRANTY: | ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills  |
| STAIN RESISTANT WARRANTY:  | XGUARD with 15 Year Limited Warranty Against Staining  |

**PRODUCT TESTING:**

|                                       |                              |
|---------------------------------------|------------------------------|
| RADIANT PANEL (ASTM E-648):           | Class I (Direct Glue)        |
| SMOKE CHAMBER (ASTM E-662):           | Less than 450 (Flaming Mode) |
| METHENAMINE PILL TEST (ASTM D-2859):  | Passes                       |
| DIMENSIONAL STABILTY AACHEN TEST:     | Passes                       |
| ELECTROSTATIC PROPENSITY (AATCC 134): | Less than 3.0 KV             |

**RECOMMENDED ADHESIVE:**

|                          |  |
|--------------------------|--|
| RELEASEABLE ADHESIVE:    | Mannington Infinity Pressure Sensitive Adhesive            |
| CRI GREEN LABEL PLUS ID: | GLP70522   |
| VOC LIMITS:              | Meets SCAQMD Rule #1168                                    |
| BOND WARRANTY:           | Lifetime Limited Warranty When Used With Mannington Carpet |

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.