

PHYSICAL CONSTRUCTION:

| | |
|----------------------|--|
| CONSTRUCTION: | Patterned Loop (Non-Ortho Phthalate Construction) |
| FACE FIBER: | Invista Antron Legacy Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5 |
| DYE METHOD: | Solution / Yarn |
| GAUGE: | 5/64 |
| STITCHES PER INCH: | 10 |
| PILE THICKNESS: | .143 Inches |
| TUFTED YARN WEIGHT: | 22 Ounces Per Square Yard |
| DENSITY: | Average Density =5,538 ; Weight Density = 121,846 |
| PRIMARY BACKING: | 100% Synthetic |
| SECONDARY BACKING: | Infinity Modular Reinforced Composite Closed Cell Polymer |
| STANDARD SIZE: | 24" X 24" Modular Tiles |
| INSTALLATION METHOD: | Monolithic or Horizontal Brick Ashlar |

ENVIRONMENTAL:

| | |
|---|--|
| RECYCLED CONTENT: | Contains Pre-Consumer Recycled Content |
| MANUFACTURE LOCATION: | Calhoun, Georgia 30701 USA |
| NSF / ANSI-140 CERTIFICATION: | Gold |
| CRI GREEN LABEL PLUS ID: | GLP7616 |
| 3 rd Party Certified Product Specific Type III EPD | |

WARRANTIES:

| | |
|----------------------------|--|
| WARRANTY: | Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection |
| BLEACH RESISTANT WARRANTY: | ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills |
| STAIN RESISTANT WARRANTY: | XGUARD with 15 Year Limited Warranty Against Staining |

PRODUCT TESTING:

| | |
|---------------------------------------|------------------------------|
| RADIANT PANEL (ASTM E-648): | Class I (Direct Glue) |
| SMOKE CHAMBER (ASTM-E-662): | Less than 450 (Flaming Mode) |
| METHENAMINE PILL TEST (ASTM D-2859): | Passes |
| DIMENSIONAL STABILTY AACHEN TEST: | Passes |
| ELECTROSTATIC PROPENSITY (AATCC 134): | Less than 3.0 KV |

RECOMMENDED ADHESIVE:

| | |
|--------------------------|--|
| RELEASEABLE ADHESIVE: | Mannington Infinity Pressure Sensitive Adhesive |
| CRI GREEN LABEL PLUS ID: | GLP70522 |
| VOC LIMITS: | Meets SCAQMD Rule #1168 |
| BOND WARRANTY: | Lifetime Limited Warranty When Used With Mannington Carpet |

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Most products contain a higher percentage of recycled content than the minimums listed above. Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.