

Style	Wood	Abstract & Stone
Construction	Luxury Vinyl Tile Non-ortho Phthalate	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B
Total Thickness	0.080" (2.0 mm)	0.080" (2.0 mm)
Wear Layer Thickness	12 mil (0.30 mm)	12 mil (0.30 mm)
Wear Layer	Enhanced Urethane	Enhanced Urethane
Edge Treatment	Square	Square
Sizes	4" x 36" (102 x 915 mm) 6" x 36" (152 x 915 mm) Sizes are style dependent; refer to Product Availability Chart	18" x 18" (457 x 457 mm)
Colors	16	12
Packaging	4" x 36" - 36 pcs, 36 ft ² (3.345 m ²), 33.84 lbs (15.35 kg) 6" x 36" - 24 pcs, 36 ft ² (3.345 m ²), 23.29 lbs. (10.56 kg)	16 pcs, 36 ft ² (3.345 m ²), 23.29 lbs (10.56 kg)
Adhesive	Porous & Non-porous Substrates: V-95 Full Spread 2-part Epoxy V-88 Full Spread, Transitional Pressure Sensitive, High Moisture XpressStep for LVT & Sheet Vinyl Full Coverage Spray XpressStep Premium for LVT Full Coverage High Moisture Spray Porous Substrates Only: V-82 Full Spread Note: Must use V-95, XpressStep or XpressStep Premium adhesive under hospital beds and heavy rolling load areas. Use V-95 where higher risk of topical moisture would be a concern.	
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.	
Testing		
HUD/FHA	Passes	
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break	
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft	
Squareness (ASTM F540)	Passes - Max 0.010"	
Static Load (ASTM F970 mod.)	Passes - 1,000 PSI; Residual Indent ≤ 0.005"	
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Resistance to Light (ASTM F1515)	Passes	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
Product Declarations	EPD	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; IEQc2 - Low Emitting Materials	
mindful MATERIALS Manufacturing	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered	
Warranty		
Limited 10 Year Light Commercial Warranty		