

Style	Flow, Intersect, Streamline
Construction	Heterogeneous Sheet (Non-ortho phthalate construction)
Classification	ASTM F1303 Type I, Grade 1, Class B
Total Thickness	0.080" (2.03 mm)
Wear Layer Thickness	0.020" (0.51 mm)
Wear Layer	Quantum Guard Elite®
Width	6' (1.83 m), 9' (2.75 m), 12' (3.66 m)
Colors	10 each style
Pattern Repeat	36" L x 72" W
Packaging	6' - 30-50 yd <sup>2</sup> (25.0-41.8 m <sup>2</sup> ) 9' - 30-75 yd <sup>2</sup> (25.0-62.7 m <sup>2</sup> ) 12' - 30-100 yd <sup>2</sup> (25.0-83.6 m <sup>2</sup> )
Weight	4.7 lbs/yd <sup>2</sup> (2.55 kg/m <sup>2</sup> )
Adhesive	<b>Porous and Non-porous Substrates:</b> <b>V-88</b> Full Spread, Transitional Pressure Sensitive, High Moisture <b>V-95</b> Full Spread, 2-part Epoxy <b>XpressStep</b> for LVT & Sheet Vinyl Full Coverage Spray <b>Porous Substrates Only:</b> <b>V-82</b> Full Spread, Acrylic Base <b>Note:</b> Must use V-95 or XpressStep adhesive under hospital beds and heavy rolling load areas. Use V-95 in Operating Rooms or where higher risk of topical moisture would be a concern.
QuickStix®	Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.
Seam Method	Mannington Commercial Weld Rods or MLG-33 Chemical Seam Sealer. Mannington Seam Coater Pen for high traffic areas. <b>Note:</b> Heat welding is the recommended procedure for healthcare and high traffic applications.
<b>Testing</b>	
HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"
Rolling Resistance/Caster Chair (ISO 4918)	25,000 Cycles, No Significant Change
Short Term Residual Indentation (ASTM F1914/F1303)	Passes - Must be < 0.012"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Acoustic STC (ASTM E90)	63 - 6" Concrete with Drop Ceiling
Resistance to Light (ASTM F1515)	Passes - < 8 Delta E Color Change
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change
<b>Environmental Data</b>	
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; IEQc2 - Low Emitting Materials Visit mM Origin website, <a href="http://mindfulmaterials.origin.build">mindfulmaterials.origin.build</a> , for current transparency information
mindful MATERIALS Manufacturing	Salem, NJ (USA) - ISO 14001 EMS Registered
<b>Warranty</b>	
	Limited 10 Year Commercial Warranty Limited 10 Year Quantum Guard Elite® Wear Warranty

**Note:** Visual/Color variations can occur from roll to roll. This variation does not affect product performance.

## Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit [manningtoncommercial.com](http://manningtoncommercial.com)