

PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Graphic Loop Pile
FACE FIBER:	Invista Antron Legacy Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5
DYE METHOD:	Solution 63% / Yarn 37%
GAUGE:	1/10
STITCHES PER INCH:	12
PILE THICKNESS:	.102 Inches
TUFT DENSITY:	120
TUFTED YARN WEIGHT:	26 Ounces Per Square Yard
DENSITY:	Average Density = 9,176; Weight Density = 238,586
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	UltraBac RE with Minimum 10% Recycled Content and Lifetime Warranty Standard
STANDARD SIZE:	12' Width
PATTERN REPEAT:	None

ENVIRONMENTAL:

RECYCLED CONTENT:	Minimum 10% Post-Consumer Recycled Content by Total Product Weight*
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Platinum
CRI GREEN LABEL PLUS ID:	GLP2278

WARRANTIES:

WARRANTY:	Lifetime Limited Warranty, Covering Face Wear, Delamination, Tuft Bind, Unraveling, and Static Protection
BLEACH RESISTANT WARRANTY:	ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM-E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

RECOMMENDED ADHESIVE:

MULTI-PURPOSE ADHESIVE:	Mannington Ultra Adhesive
CRI GREEN LABEL PLUS ID:	GLP70513
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	10 Year Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.