

MANNINGTON ASSURANCE II

	CONSTRUCTION	Homogeneous Slip Resistant Commercial Sheet
	AVAILABLE SIZE	Available in 6' (1.83 m)
	OVERALL THICKNESS	.080" (2.03 mm)
	WEAR LAYER THICKNESS	.080" (2.03 mm)
	WEIGHT PER SQUARE YARD	6.5 lbs/yd ² (3.53 kg/m ²). For packing weight, it includes interleaf of 0.40 lbs. per sq. yd.(0.22 kg/m2)
	SQUARE YARD PER ROLL (MIN-MAX)	30 - 68 sq. yds. (25.1 - 56.9 sq. m.)
	3RD PARTY CERTIFICATIONS	FloorScore, NSF/ANSI 332 Platinum
	WARRANTY	This product is backed by our Limited 5 Year Commercial Warranty and Limited 5 Year Quantum Guard® HP Wear Warranty.
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
STATIC LOAD LIMIT		750 PSI
SPECIFICATION (ASTM F1913)		Exceeds
HUD/FHA REQUIREMENTS		Meets or exceeds
AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)		Meets or exceeds ADA Guidelines
COEFFICIENT OF FRICTION (COF)		≥ 0.5 Leather; 0.6 Rubber
FLOORING RADIANT PANEL (ASTM E648)		≥ .45 watts/cm ² , Passes - Class 1
N.B.S. SMOKE CHAMBER (ASTM E662)		< 450, Passes
INSTALLATION ADHESIVE		Porous Substrate: V-82 Full Spread Non-Porous Substrate: V-95 Full Spread, 2 Part Epoxy Porous & Non-Porous Substrate: M-Guard V-88 Full Spread, Transitional Pressure Sensitive, High Moisture or XpressStep for Sheet Vinyl Note: Must use V-95 or XpressStep for Sheet Vinyl adhesive under hospital beds, OR tables and heavy rolling loads or where high performance is needed.
SEAM METHOD		Mannington Commercial Solid Weld Rods. Heat welding is the recommended procedure for healthcare and high traffic applications.

Floor designs copyrighted by Mannington Mills, Inc. 2014. For complete specifications, visit manningtoncommercial.com.

