

**Product Specifications**  
**MAINBOARD -- INFINITY 2 MODULAR****PHYSICAL CONSTRUCTION:**

---

CONSTRUCTION:	Pattern Loop (Non-Ortho Phthalate Construction)
FACE FIBER:	Invista Antron Lumena Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5
DYE METHOD:	Solution
GAUGE:	5/64
STITCHES PER INCH:	9.5
PILE THICKNESS:	.108 Inches
TUFTED YARN WEIGHT:	20 Ounces Per Square Yard
DENSITY:	Average Density =6,667; Weight Density = 133,334
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	Infinity 2 Modular Reinforced Composite Closed Cell Polymer
STANDARD SIZE:	24" X 24" Modular Tiles
INSTALLATION METHOD:	Horizontal Brick Ashlar

**ENVIRONMENTAL:**

---

RECYCLED CONTENT:	Contains Pre-Consumer Recycled Content
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Gold
CRI GREEN LABEL PLUS CERTIFIED	
ISO 14001 CERTIFIED	
3 <sup>RD</sup> PARTY CERTIFICATION:	Type III EPD (Environmental Product Declaration) V2.1 HPD (Health Product Declaration)

**WARRANTIES:**

---

WARRANTY:	Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection
BLEACH RESISTANT WARRANTY:	ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

**PRODUCT TESTING:**

---

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
DIMENSIONAL STABILTY AACHEN TEST:	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

**RECOMMENDED ADHESIVE:**

---

RELEASEABLE ADHESIVE:	Mannington Infinity Pressure Sensitive Adhesive
CRI GREEN LABEL PLUS ID:	GLP70522
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.