

Style	Radius Modular (Non-Ortho Pthalate)	Range Modular (Non-Ortho Pthalate)	TSN Modular (Non-Ortho Pthalate)
Construction	Patterned Loop	Patterned Loop	Patterned Loop
Face Fiber	ECONYL® 100% regenerated Type 6 Nylon	ECONYL® 100% regenerated Type 6 Nylon	ECONYL® 100% regenerated Type 6 Nylon
Dye Method	Solution	Solution	Solution
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	9 (35.43 per 10 cm)	9.33 (36.73 per 10 cm)	9.16 (36.06 per 10 cm)
Density	5,538 (205.78 Kg/m³)	5,538 (205.78 Kg/m³)	5,538 (205.78 Kg/m³)
Pile Thickness	0.091" (2.31 mm)	0.091" (2.31 mm)	0.091" (2.31 mm)
Backing Type	Infinity® Modular	Infinity® Modular	Infinity® Modular
Sizes	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	11	11	11
Pattern Repeat	N/A	N/A	N/A
Packaging	6.22 Sq. Yards / 14 Tiles	6.22 Sq. Yards / 14 Tiles	6.22 Sq. Yards / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Shuffled / Horizontal Brick Ashlar	Shuffled / Horizontal Brick Ashlar	Shuffled
<b>Testing</b>			
Dimensional Stability AACHEN Test	Passes	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 KV	Less than 3.0 KV	Less than 3.0 KV
Radiant Panel (ASTM E648)	P ≥ 0.45 watts/cm², Passes (Class 1)	≥ 0.45 watts/cm², Passes (Class 1)	≥ 0.45 watts/cm², Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D-2859)	Passes	Passes	Passes
Hexapod (ASTM D5252) TARR Rating	3.5	3.5	3.5
<b>Environmental Data</b>			
NSF / ANSI-140 Certification	Infinity® Modular - Gold	Infinity® Modular - Gold	Infinity® Modular - Gold
Recycled Content	Contains Pre Consumer Content		
Indoor Air Quality	CRI Green Label Plus Certified		
Recyclability	LOOP®		
LEED Scoreboard	May contribute to LEED Credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials		
mindful Materials	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information		
Manufacturing	N/A		
<b>Warranty</b>			
	Limited Lifetime Wear & Backing Limited 15-year XGUARD® Stain Resistant Limited 15 Year ColorSafe® Bleach Resistant		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller castors to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make final selection from actual swatch. To order samples go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.

## Crafted with purpose

For more information, contact your local Mannington representative or visit [manningtoncommercial.com](http://manningtoncommercial.com)