

Resilient Adhesives	Product Applications	Size/Mat #	Coverage	Trowel/Description	MVER/ CC	RH	pH
Sheet Vinyl & LVF							
width x depth x spacing							
V-81 (Premium Latex)	Biospec FB, Insight Plus, Terene	(4) 1 gallon - 12252 4 gallon - 12251	135 sf/gal - porous 180 sf/gal - non-porous	1/16 x 1/16 x 1/16 "U"- porous 1/16 x 1/32 x 1/32 "U" - non-porous	5 lbs.	80%	9pH
V-82 (Acrylic Base)	Assurance II, Biospec MD/RE/SR, Entwined, Paradigm, Realities II, Vivendi II & all LVF	(4) 1 gallon - 61390 4 gallon - 15784	150-200 sf/gallon	1/16 x 1/32 x 1/32 "U" notch	8 lbs.	85%	10pH
V-88 (Transitional Pressure Sensitive)	Assurance II, Biospec MD/RE/SR, Entwined, Paradigm, Realities II, Vivendi II & all LVF	4 gallon - 186054	250 sf/gal - porous 350 sf/gal - non-porous	1/16 x 1/32 x 1/32 "U" - porous 1/16 x 1/32 x 5/64 "U"- non-porous	8	90%	10pH
V-95 (2 Part Epoxy)	Assurance II, Biospec MD/RE/SR, Entwined, Paradigm, Realities II, Vivendi II & all LVF	1 gallon - 55788	185-245 sf/gallon	1/16 x 1/32 x 1/32 "U" notch	8 lbs.	90%	11pH
MT-711 (Acrylic based Pressure Sensitive)	Insight Plus GB - ONLY	1 gallon - 22857 4 gallon - 3143	150 sf/gallon	1/16 x 1/32 x 1/32 "U" notch	8 lbs.	90%	11pH
XpressStep - Sheet Vinyl	Assurance II, Biospec MD/SR/RE, Entwined, Paradigm, Realities II and Vivendi II	6 cans/ctn - 284394	150-185 sf/can	SPRAY	8 lbs.	90%	11pH
XpressStep - LVF	LVF	6 cans/ctn - 277856	150-185 sf/can	SPRAY	8 lbs.	90%	11pH
XpressStep Premium- LVF High Moisture	LVF	6 cans/ctn - 277855	100-125 sf/can	SPRAY	8 lbs.	90%	11pH
LVF Adhesive-Free System							
QuickStix	Standard LVF	N/A	N/A	Peel N Stick	18	99%	12pH
LVF Floating System							
City Park (Solid Core) Floor Armour	LVF	N/A	N/A	Floating Floor	8	90%	9pH
Seam Sealers & Welds							
MCS-42	Biospec MB/FB/RE and Terene	1 pint - 186836 12 pints/ctn - 15783	400-600 lineal ft / pint	For all sheet goods except urethane-based wearlayers			
MLG-33 (urethane sealer)	Assurance II, Biospec SR, Entwined, Insight Plus, Insight Plus GB, Realities II, Paradigm, Vivendi II	1 oz can - 186873 (6) 1 oz cans - 12212	70 lineal ft/kit	2-part sealer for urethane wearlayers			
QGHP Seam Coater Pen	All commercial sheet vinyl	1 pen - 180626	300 lineal ft/pen	QG topical protection for heat welded seams			
VST-96	Bottle used for the seam sealer	1 bottle - 186871 6 bottles/ctn - 12210	4 oz. clear bottles	Applicator bottle			
Weld Rod (solid)	All commercial sheet vinyl except Insight Plus	spool	165 lineal feet/spool	Preffered commercial installation method			
Primer							
Mannington Universal Primer	Optional for all products. Required for Quick Stix	4gal - 293549 1gal - 293552 4@1gal - 293550	38 -45 sy/yd or (350-400 sf/gal)	Medium nap paint roller. For large jobs apply with; garden sprayer, airless rig or regular paint sprayer. Primer/pH Blocker/Neutralize Alkali /Integra HP /Installations specific to FreLock Tabs			

All spread rates per pail considered with smooth / clean sub-floor and maximum coverage