

Resilient Adhesives	Product Applications	Size/Mat #	Coverage	Trowel/Description	MVER/ CC	RH	pH
<b>Sheet Vinyl &amp; LVF</b>							
width x depth x spacing							
MT-711 (Acrylic based Pressure Sensitive)	Insight Plus GB - <u>ONLY</u>	1 gallon - 22857 4 gallon - 3143	150 sf/gallon	1/16 x 1/32 x 1/32 "U" notch	3 lbs.	75%	9pH
V-81 (Premium Latex)	Biospec FB, Insight Plus, Terrene	(4) 1 gallon - 12252 4 gallon - 12251	135 sf/gal - porous 180 sf/gal - non-porous	1/16 x 1/16 x 1/16 "U" - porous 1/16 x 1/32 x 1/32 "U" - non-porous	5 lbs.	80%	9pH
V-82 (Acrylic Base)	Assurance II, Biospec MD/RE/SR, City Hub, Color Anchor, Entwined, Paradigm, Realities II, Vivendi II & all LVF	(4) 1 gallon - 61390 4 gallon - 15784	150-200 sf/gallon	1/16 x 1/32 x 1/32 "U" notch	3 lbs.	75%	9pH
V-88 Sheet (Transitional Pressure Sensitive)	Assurance II, Biospec MD/RE/SR, City Hub, Color Anchor, Entwined, Paradigm, Realities II, Vivendi II	4 gallon - 186054	250 sf/gal - porous 350 sf/gal - non-porous	1/16 x 1/32 x 1/32 "U" - porous 1/16 x 1/32 x 5/64 "U" - non-porous	Sheet New Construction Slab		
					10 lbs.	95%	12pH
V-88 LVT (Transitional Pressure Sensitive)	Color Anchor LVT, Divergent, Mannington Select, Natures Paths, Primary Elements, Walkway, Walkway 20				LVT New Construction Slab		
					12 lbs	99%	12pH
V-88 Sheet & LVT (Transitional Pressure Sensitive)	Assurance II, Biospec MD/RE/SR, City Hub, Color Anchor, Entwined, Paradigm, Realities II, Vivendi II & all LVF				Sheet & LVT Old / Renovation Slab		
					8 lbs.	90%	10pH
V-95 (2 Part Epoxy)	Assurance II, Biospec MD/RE/SR, City Hub, Color Anchor, Entwined, Paradigm, Realities II, Vivendi II & all LVF	1 gallon - 55788	185-245 sf/gallon	1/16 x 1/32 x 1/32 "U" notch	3 lbs.	75%	9pH
XpressStep - Sheet Vinyl & LVF	Assurance II, Biospec MD/SR/RE, City Hub, Color Anchor, Entwined, Paradigm, Realities II and Vivendi II & all LVF	6 cans/ctn - 391074	150-185 sf/can	SPRAY	10 lbs.	95%	11pH
XpressStep Premium- LVF High Moisture	LVF	6 cans/ctn - 277855	100-125 sf/can	SPRAY	10 lbs.	98%	12pH
<b>LVF Adhesive-Free System</b>							
QuickStix	Standard LVF	N/A	N/A	Peel N Stick	18 lbs.	99%	12pH
<b>LVF Floating System</b>							
City Park (Solid Core) Floor Armour	LVF	N/A	N/A	Floating Floor	8 lbs.	90%	9pH
<b>Seam Sealers &amp; Welds</b>							
MCS-42	Biospec MD/FB/RE/SR, Color Anchor Prism, and Terrene	1 pint - 186836 12 pints/ctn - 15783	400-600 lineal ft / pint	For all sheet goods except urethane-based wearlayers			
MLG-33 (urethane sealer)	Assurance II, City Hub, Color Anchor Arc, Entwined, Insight Plus, Insight Plus GB, Realities II, Paradigm and Vivendi II	1 oz can - 186873 (6) 1 oz cans - 12212	70 lineal ft/kit	2-part sealer for urethane wearlayers			
QGHP Seam Coater Pen	All commercial sheet vinyl	1 pen - 180626	300 lineal ft/pen	QG topical protection for heat welded seams			
VST-96	Bottle used for the seam sealer	1 bottle - 186871 6 bottles/ctn - 12210	4 oz. clear bottles	Applicator bottle			
Weld Rod (solid)	All commercial sheet vinyl except Insight Plus	spool	165 lineal feet/spool	Preferred commercial installation method			
<b>Primer</b>							
Mannington Universal Primer	Optional for all products. Required for Quick Stix	4gal - 293549 1gal - 293552 4@1gal - 293550	38 -45 sy/yd or (350-400 sf/gal)	Medium nap paint roller. For large jobs apply with; garden sprayer, airless rig or regular paint sprayer. Primer/pH Blocker/Neutralize Alkali /Integra HP /Installations specific to FreLock Tabs			

All spread rates per pail considered with smooth / clean sub-floor and maximum coverage