

# TACKIFIER

A water-based, solvent-free tackifier with very low emissions, specially suitable for installing Spacia Access tiles onto a wide range of substrates.

## BENEFITS

A water-based, solvent-free tackifier with very low emissions, specially suitable for installing Spacia Access tiles onto a wide range of substrates, including concrete, stone, terrazzo, ceramic, raised access floors, plywood and existing resilient floors. In areas where large variations in temperature may occur, such as floors exposed to direct sunlight, then Amtico's Universal 2 Part Adhesive should be used to install Spacia Access.

## PREPARATION

Substrate must be sound, smooth, dry and free from any contaminants that will affect adhesion. Any previously applied sealers, waxes, or floor finishes of any kind must be completely removed. The substrate must be free from all existing maintenance products before the Tackifier is applied. A suitable primer may be required on non-porous sub-floors.

## APPLICATION

Shake the container before removing lid. Do not dilute tackifier with water. Apply to surface with a fine foam roller to give a consistent coverage, avoiding puddling. Allow the tackifier to dry completely to a transparent film before laying the Spacia Access floor tiles.

## CLEANING

Tackifier residues can be removed with a cloth dampened with water.

## COVERAGE

Up to 300 sq ft/gallon 6.1 m<sup>2</sup>/L

## OPEN TIME

30 to 60 minutes

## SHELF LIFE

12 months from date of manufacture, provided product is stored in unopened containers in cool and dry conditions.

Technical Data Sheet and Material Safety Data Sheet are available on request.

Protect from frost.

See [manningtoncommercial.com](http://manningtoncommercial.com) for MSDS and more information.

