

MR-911 Acrylic Adhesive is a water-resistant, solvent free, high strength water based acrylic latex adhesive specially formulated for the installation of Mannington Commercial rubber flooring and vinyl and rubber stair treads on clean porous surfaces only. MR-911 is suitable for use on suspended approved wood floors (APA), dry concrete floors and staircases above or on grade where concrete substrate moisture does not exceed manufacturer's recommendations.

PHYSICAL PROPERTIES

Wt. /Gallon (lbs) 9.7

Consistency White paste

Freeze thaw 5 cycles @ 0 degrees F

Shelf life 1 yr @70F in unopened container

DIRECTIONS

1. All surfaces must be clean, dry, and free of dust, grease, paints, oils, curing compounds, sealers, or any other foreign material which may interfere with proper adhesion.
2. Cracks and uneven surfaces must be filled with cement based patching compound.
3. Mannington MR-911 is recommended for porous applications.
4. Once troweled the adhesive should be allowed to remain open (flash-off) for approximately 5-10 minutes before placement of the flooring material. Do not allow adhesive to "skin over" before laying the flooring into the adhesive.
5. Once placed, the material should be rolled immediately utilizing a 100 pound three-section roller.
6. It is the responsibility of the user to determine whether or not the sub-floor to be covered is porous. To determine if a sub-floor is porous, place two droplets of water in various areas. If the sub-floor is porous, the water will be absorbed within a few seconds.

COVERAGE

Approx. 100 sq. ft. /gal with 1/16" square notch

Approx. 150 sq. ft. /gal with 1/16"x1/16"x1/16" V-notch

CLEAN-UP

Remove wet adhesive immediately with a damp cloth. Use Mineral Spirits to remove dried adhesive

DO NOT APPLY SOLVENT DIRECTLY TO FLOORING MATERIAL.

FOR MORE INFORMATION REFER TO MATERIAL SAFETY DATA SHEET.

KEEP OUT OF REACH OF CHILDREN.