

Specification

FreLock Tabs (3x3) Specification

For Installation of Mannington's Infinity, Infinity 2, Infinity 2 MG & Infinity RE Modular Backings

CONSTRUCTION

Double-sided tape with fabric carrier

Backing:	Fabric Carrier
Adhesive:	Acrylic Dispersion
Liner:	Polyester, Silicone-coated

SPECIFICATIONS

Size:	3" x 3" (Perforated Tab)
Roll Length:	130 feet
Tabs per Roll:	500
Coverage:	With 24" x 24" modular tile: 150 sq. yds. (Monolithic or Quarter Turn) 100 sq. yds. (All other methods) With 18" x 36" or 12" x 48" modular plank: 110 sq. yds. (Monolithic) 80 sq. yds. (All other methods)
Thickness:	8.6 mil (without any liners), each liner ~3.5 mil
SAP Order Code:	385692 – 1 Roll
Shelf Life:	18 months from manufacture date on unopened containers
Moisture Limits:	90% RH / 8 lbs. CC / 10 pH (Infinity, Infinity 2, and Infinity RE Backing) 99% RH / CC Not Applicable / 12 pH (Infinity 2 MG Backing) Note: 99% RH is for floating installations only. Not applicable to double stick.

ADVANTAGES

- Glueless installation
- Easy peel cover
- Low V.O.C / Low odor
- High tac
- Quick stick – No flash off time
- Releasable
- Use for temporary installations
- Good operating temperature range
- Conforms well to irregular surfaces

Note: Mannington Universal Primer is required with double stick installation method.

Specifications are subject to nominal manufacturing variances. Specifications are subject to change without notice when shortages occur or when technological advancements provide improved product performance.