

MANNINGTON COMMERCIAL

SPECIFICATION FreLock Tabs

(For Installation of Mannington's Infinity Modular and Infinity RE Modular Backings)

CONSTRUCTION:

Double-faced adhesive membrane	
Backing:	½ mil polyester (PET) film
Adhesive:	Solvent Acrylic
Liner:	Bleached kraft paper

SPECIFICATIONS:

Width:	3 inches
Roll Length:	108 feet
Tabs per Roll:	130
Tab Size:	3" x 10" (Perforated tab)
Coverage:	50 - 55 sq. yds. (Monolithic, Quarter Turn, or Random) 40 - 45 sq. yds. (Horizontal Ashlar)
Thickness:	4 mils
Service Temperature Range:	-40° F to 194°F
SAP Order Code:	293403 – 1 Roll 293402 – 1 Carton (16 Rolls)
Moisture Limits:	85% RH / 5 lbs. CC / 9 pH

ADVANTAGES:

1. Glue less Installation
2. Easy peel cover
3. Low V.O.C
4. High Tac
5. Quick Stick – No flash off time
6. Releasable
7. Good operating temperature range
8. Conforms well to irregular surfaces.

**specifications are subject to nominal manufacturing variances

**specifications are subject to change without notice when shortages occur or when technological advances provide improved product performance.