

Specification

FreLock Tabs (3x10) Specification

For Installation of Mannington's Infinity, Infinity 2 & Infinity 2 MG Modular Backings

CONSTRUCTION

Double-faced adhesive membrane

Backing:	½ mil Polyester (PET) Film
Adhesive:	Solvent Acrylic
Liner:	3 mil Polyester

SPECIFICATIONS

Size:	3" x 10" (Perforated Tab)
Roll Length:	108 feet
Tabs per Roll:	130
Coverage:	With 24" x 24" modular tile: 40-45 sq. yds. (Monolithic or Quarter Turn) 30-35 sq. yds. (All other methods) With 18" x 36" or 12" x 48" modular plank: 30-35 sq. yds. (Monolithic) 25-30 sq. yds. (All other methods)
Thickness:	4 mil
SAP Order Code:	293403 – 1 Roll 293402 – 1 Carton (16 Rolls)
Shelf Life:	18 months from manufacture date on unopened containers
Moisture Limits:	90% RH / 8 lbs. CC / 10 pH (Infinity and Infinity 2 Backing) 99% RH / CC Not Applicable / 12 pH (Infinity 2 MG Backing) Note: 99% RH is for floating installations only. Not applicable to double stick.

ADVANTAGES

- Glueless installation
- Easy peel cover
- Low V.O.C / Low odor
- High tac
- Quick stick – No flash off time
- Releasable
- Use for temporary installations
- Good operating temperature range
- Conforms well to irregular surfaces

Note: Mannington Universal Primer is required with double stick installation method.

Specifications are subject to nominal manufacturing variances. Specifications are subject to change without notice when shortages occur or when technological advancements provide improved product performance.