

Mannington Assure

Mannington Assure is a solvent-free, polymer-based sealer designed to isolate adhesive residue on sub floors. This includes old adhesives, acrylic, SBR and cutback, present before the installation of new flooring.

Features

- Solvent Free, Fast Drying floor sealer
- Roller Application with 3/4" (9mm) nap roller
- CRI Green Label Plus Certified
- Freeze/Thaw Stable

Preparation

Substrate must be sound, clean and free of loose dust, dirt, oil, grease, paint, curing compound, concrete sealers, loosely bonded toppings, or any other foreign substance that might limit or prohibit a good bond. Substrate, adhesive and carpet must be acclimated in an enclosed building with the HVAC operational and running for at least 48 hours before, during and after the installation. Subfloor must be tested in accordance with ASTM protocol to determine if chemical pH and RH levels are suitable.

Installation

Mannington Assure can be applied using a 3/4" (9 mm) nap roller. After application of the material to the substrate allow to dry clear and become non-tacky to the touch, approximately 2-3 hours depending on the temperature and relative humidity. Relative humidity of above 65% will slow drying time. Allow 4 hours dry time before installing new flooring. Please refer to the Mannington Assure Installation guidelines for complete details.

Approximate Coverage*

With a 3/4" (9mm) nap roller: 250 to 300 sq. ft. per U.S. gal. (6.12 to 7.35 m²/L)

*Coverage shown is for estimating purposes only. Actual jobsite coverage may vary according by application method, substrate conditions and actual thickness applied. Please refer to the complete installation guidelines for additional information.

Warranty

Mannington Assure is backed by a 10 year limited warranty

Note

Refer to technical and material safety data sheets for complete information regarding uses, application, limitations and safety.

Installation Guidelines

To obtain Mannington's Installation Guidelines, specifications and SDS, contact Mannington Commercial.

ph: 800-241-2262
manningtoncommercial.com

ManningtonAssure Sealer • Roller Application • Solvent Free
4 U.S. Gallons (15.14 Liters) • Order Code 390279
